

View Online at <https://aerobasegroup.com/nsn/5990-00-939-8229>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

2.3560 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.5620 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

11

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

54.0 milliamperes

Rotor Input Electrical Power Rating:

82.0 milliwatts

Zro Impedance Magnitude In Ohms:

2130.00

Zro Impedance Angle In Deg:

82.40

Zso Impedance Magnitude In Ohms:

1083.00

Zso Impedance Angle In Deg:

91.10

Phase Shift Angle In Deg:

4.300 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

3.90 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

38.00

Alignment Hole Quantity:

4

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7940 inches

Terminal Location:

Rear

Shaft Type:

Round single shaft

Alignment Hole Depth:

0.1250 inches

Transformation Ratio:

0.783 stator to rotor

Alignment Hole Bolt Circle Diameter:

0.8120 inches

Terminal Type And Quantity:

5 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800