

View Online at <https://aerobasegroup.com/nsn/5990-00-939-8230>

**Body Material:**

Steel, corrosion resisting

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.0995 inches and 1.0000 inches

**Pilot Diameter:**

Between 0.6245 inches and 0.6250 inches

**Overall Length:**

2.3560 inches

**Flange Diameter:**

Between 1.0570 inches and 1.0650 inches

**Flange Thickness:**

0.0930 inches

**Undercut Diameter:**

0.9750 inches

**Undercut Width:**

0.0500 inches

**Shaft Diameter:**

0.1195 inches single shaft and 0.1200 inches single shaft

**Shaft Length:**

0.5600 inches single shaft

**Maximum Temperature Rise:**

15.0 degrees celsius

**Body Size:**

11

**Rotor Input Voltage Rating In Volts:**

115.0

**Frequency In Hertz:**

400.0

**Rotor Input Current Rating:**

70.0 milliamperes

**Rotor Input Electrical Power Rating:**

1.1 watts

**Zro Resistance In Ohms:**

250.00

**Zso Resistance In Ohms:**

145.00

**Phase Shift Angle In Deg:**

4.500 input to output

**Maximum Fundamental Null Voltage In Millivolts Per Volt:**

45.00 output

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

90.00

**Electrical Error Angular Range In Minutes:**

-7.0/+7.0

**Actuator Friction Torque At Minus 55 Deg Celsius:**

6.0 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

3.0 centimeter-grams

**Torque Gradient Per Angular Deg:**

6000.0 millimeter-milligrams

**Alignment Hole Quantity:**

4

**Pilot Length:**

0.0620 inches

**Shoulder Length:**

0.0620 inches

**Mounting Surface To Terminal End Distance:**

1.7940 inches

**Terminal Location:**

Rear

**Plus J Zro Reactance In Ohms:**

1890.00

**Plus J Zso Reactance In Ohms:**

915.00

**Shaft Type:**

Round single shaft

**Alignment Hole Depth:**

0.1250 inches

**Transformation Ratio:**

0.783 rotor to stator

**Alignment Hole Bolt Circle Diameter:**

0.8120 inches

**Terminal Type And Quantity:**

5 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07800