

View Online at <https://aerobasegroup.com/nsn/5990-00-939-8890>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

Between 0.7495 inches and 0.7500 inches

Overall Length:

3.7700 inches

Flange Diameter:

0.8750 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.7600 inches

Undercut Width:

0.0570 inches

Shaft Diameter:

0.1246 inches single shaft and 0.1248 inches single shaft

Shaft Length:

1.1200 inches single shaft

Body Size:

8

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

461.0 amperes

Rotor Input Electrical Power Rating:

350.0 allqjaa3.500 microwatts

Rotor Dc Resistance In Ohms:

880.00

Stator Dc Resistance In Ohms:

20.00

Phase Shift Angle In Deg:

8.500 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

15.00

Actuator Friction Torque At Plus 25 Deg Celsius:

3.00 inch-ounces

Shaft Maximum Radial Play:

0.0008 inches

Shaft End Play:

0.0040 inches

Pilot Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

2.6500 inches

Shaft Maximum Runout:

0.0008 inches

Terminal Location:

Rear

Shaft Type:

Round single shaft

Shaft Radial Play Determining Weight:

4.0 ounces

Shaft End Play Determining Weight:

8.0 ounces

Special Features:

Includes clutch

Precious Material And Location:

Terminal surfaces gold and terminals silver

Precious Material:

Gold and silver

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800