NSN 5990-00-943-0316

Control Transformer Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-943-0316

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

Between 1.8300 inches and 1.8800 inches

Flange Diameter:

0.7500 inches

Flange Thickness:

Between 0.0590 inches and 0.0650 inches

Undercut Diameter:

0.6910 inches

Undercut Width:

Between 0.0590 inches and 0.0650 inches

Shaft Diameter:

0.1245 inches front shaft and 0.1247 inches front shaft

Shaft Length:

0.4000 inches front shaft and 0.4300 inches front shaft

Schematic Diagram Designator:

Err-090

Body Size:

Frequency In Hertz:

400.0

Actuator Friction Torque At Minus 55 Deg Celsius:

6.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.00 centimeter-grams

Shaft Radial Play Test Point:

0.125 inches

Shaft Maximum Radial Play:

0.0008 inches

Shaft End Play:

Between 0.0005 inches and 0.0015 inches

Pilot Length:

0.0380 mils and 0.0430 centimeters

Mounting Surface To Terminal End Distance:

1.2410 inches

Shaft Maximum Runout:

0.0008 inches

NSN 5990-00-943-0316 Control Transformer Synchro - Page 2 of 2



Terminal Location:
Side
Shaft Type:
Round both shafts
Shaft Radial Play Determining Weight:
4.0 ounces
Shaft End Play Determining Weight:
3.0 ounces
Special Features:
Rear shaft dim. 0.2090 in. Maximum Ig, 0.0933 in. Min, 0.0935 in. Maximum dia
Test Data Document:
39954-926c327 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Filg:
407800