

View Online at <https://aerobasegroup.com/nsn/5990-00-945-1591>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round b

Shoulder Diameter:

1.3120 inches

Pilot Diameter:

0.8750 inches

Overall Length:

2.4700 inches

Flange Diameter:

1.4370 inches

Flange Thickness:

0.0930 inches

Undercut Width:

0.0780 inches

Shaft Diameter:

0.1872 inches single shaft

Shaft Length:

0.5000 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

15

Stator Input Voltage Rating In Volts:

90.0

Stator Input Current Rating:

75.0 milliamperes

Stator Input Electrical Power Rating:

3.5 watts

Frequency In Hertz:

60.0

Zro Resistance In Ohms:

500.00

Zso Resistance In Ohms:

620.00

Phase Shift Angle In Deg:

16.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

75.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

125.00

Electrical Error Angular Range In Minutes:

-8.0/+8.0

Spline Tooth Quantity:

21 single shaft

Actuator Friction Torque At Plus 25 Deg Celsius:

0.05 inch-ounces

Pilot Length:

0.0400 inches

Shoulder Length:

0.1320 inches

Mounting Surface To Terminal End Distance:

1.7980 inches

Spline Tooth Diametral Pitch:

120 single shaft

Shaft Thread Series Designator:

Unf single shaft

Shaft Thread Direction:

Right-hand single shaft

Shaft Thread Class:

Za

Terminal Location:

Rear

Shaft Thread Length:

0.2000 inches single shaft

Plus J Zro Reactance In Ohms:

1250.00

Plus J Zso Reactance In Ohms:

1020.00

Shaft Type:

Spline w/threads single shaft

Transformation Ratio:

1.154 rotor to stator

Shaft Thread Size:

0.190 inches single shaft

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800