

View Online at <https://aerobasegroup.com/nsn/5990-00-945-6709>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

Between 0.4997 inches and 0.5000 inches

Overall Length:

Between 2.0880 inches and 2.1630 inches

Flange Diameter:

Between 0.7490 inches and 0.7500 inches

Flange Thickness:

Between 0.0580 inches and 0.0650 inches

Undercut Diameter:

0.6910 inches

Undercut Width:

0.0570 inches

Shaft Diameter:

0.1198 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.6000 inches single shaft

Body Size:

8

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

96.0 milliamperes

Stator Input Electrical Power Rating:

210.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

38.00

Zso Resistance In Ohms:

28.00

Rotor Dc Resistance In Ohms:

36.00

Stator Dc Resistance In Ohms:

24.00

Phase Shift Angle In Deg:

11.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

20.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-5.0/+5.0

Actuator Friction Torque At Minus 55 Deg Celsius:

9.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Pilot Length:

0.0430 inches

Mounting Surface To Terminal End Distance:

1.3680 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

122.00

Shaft Slot Depth:

0.0150 inches single shaft and 0.0350 inches single shaft

Plus J Zso Reactance In Ohms:

114.00

Shaft Slot Width:

0.0150 inches single shaft and 0.0350 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

1.128 rotor to stator

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800