

| NSN 5990-00-945-9914 Differential Transmitter Synchro - Page 1 of 3 | AeroB |
|---|-------|
| View Online at https://aerobasegroup.com/nsn/5990-00-945-9914 | |
| Body Material: | |
| Steel, stainless | |
| Body Style: | |
| Standard round c | |
| Shoulder Diameter: | |
| Between 1.3115 inches and 1.3120 inches | |
| Pilot Diameter: | |

Between 0.8745 inches and 0.8750 inches

Overall Length: 2.4700 inches

Flange Diameter: Between 1.4320 inches and 1.4370 inches

Flange Thickness:

Undercut Diameter:

0.0930 inches

1.3120 inches

Undercut Width:

0.0780 inches **Shaft Diameter:**

0.1870 inches single shaft and 0.1872 inches single shaft

Shaft Length:

0.5400 inches single shaft

Fragility Factor:

Moderately rugged

Maximum Tempurature Rise:

20.0 degrees celsius

Body Size:

15

Stator Input Voltage Rating In Volts:

90.0

Stator Input Current Rating:

90.0 milliamperes

Stator Input Electrical Power Rating:

900.0 milliwatts

Frequency In Hertz:

400.0

Zso Impedance Magnitude In Ohms:

Between 870.00 and 1150.00

Zso Impedance Angle In Deg:

Between 79.00 and 85.00

Zrs Impedance Magnitude In Ohms:

Between 195.00 and 290.00

NSN 5990-00-945-9914

Differential Transmitter Synchro - Page 2 of 3



Zrs Impedance Angle In Deg: Between 27.00 and 37.00 Phase Shift Angle In Deg: 5.500 input to output Maximum Fundamental Null Voltage In Millivolts Per Volt: 32.00 output Maximum Total Null Voltage Output In Millivolts Per Volt: 60.00 **Electrical Error Angular Range In Minutes:** -6.0/+6.0 **Spline Tooth Quantity:** 21 single shaft **Torque Gradient Per Angular Deg:** 0.070 inch-ounces **Alignment Hole Quantity:** Pilot Length: 0.0400 inches **Shoulder Length:** 0.1320 inches **Mounting Surface To Terminal End Distance:** 1.9300 inches **Spline Tooth Diametral Pitch:** 120 single shaft **Shaft Thread Series Designator:** Unf single shaft **Shaft Thread Direction:** Right-hand single shaft **Shaft Thread Class:** 2a **Terminal Location:** Rear **Shaft Thread Length:** 0.2000 inches single shaft **Shaft Type:** Spline w/threads single shaft Alignment Hole Depth: 0.1250 inches **Transformation Ratio:** 1.154 rotor to stator

Shaft Thread Size:

1.1000 inches

0.190 millimeters single shaft

Alignment Hole Bolt Circle Diameter:

NSN 5990-00-945-9914

Differential Transmitter Synchro - Page 3 of 3



Test Data Document:

81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

| Termir | nal Typ | e And | l Qua | intity: |
|--------|---------|-------|-------|---------|
| | | | | |

6 screw

Specification Data:

81349-mil-s-20708-16 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800