

View Online at <https://aerobasegroup.com/nsn/5990-00-946-3315>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6010 inches

Flange Diameter:

Between 0.7490 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.6910 inches

Undercut Width:

0.0570 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.3600 inches single shaft and 0.3900 inches single shaft

Body Size:

8

Rotor Input Voltage Rating In Volts:

Between 0.5 and 26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

5.0 milliamperes

Rotor Input Electrical Power Rating:

16.0 milliwatts

Zro Resistance In Ohms:

2040.00

Zso Resistance In Ohms:

430.00

Zrs Resistance In Ohms:

395.00

Rotor Dc Resistance In Ohms:

230.00

Stator Dc Resistance In Ohms:

27.00

Transformation Ratio Equality In Percent:

3.0

Phase Shift Angle In Deg:

2.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

20.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Interaxis Error Angular Range In Minutes:

-5.0/+5.0

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

14.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

5.0 centimeter-grams

Pilot Length:

0.0430 inches

Mounting Surface To Terminal End Distance:

1.2410 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

5830.00

Shaft Slot Depth:

0.0200 inches single shaft and 0.0350 inches single shaft

Plus J Zso Reactance In Ohms:

1300.00

Shaft Slot Width:

0.0150 inches single shaft and 0.0350 inches single shaft

Plus J Zrs Reactance In Ohms:

575.00

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.444 rotor to stator

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800