## NSN 5990-00-959-2373

Control Transformer Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-959-2373

**Body Material:** Steel, stainless **Body Style:** Standard round c **Shoulder Diameter:** Between 0.9995 inches and 1.0000 inches **Pilot Diameter:** Between 0.6245 inches and 0.6250 inches **Overall Length:** Between 2.1240 inches and 2.1540 inches Flange Diameter: Between 1.0570 inches and 1.0650 inches Flange Thickness: Between 0.0900 inches and 0.0960 inches **Undercut Diameter:** 0.9750 inches **Undercut Width:** 0.0500 inches **Shaft Diameter:** 0.1195 inches single shaft and 0.1200 inches single shaft **Shaft Length:** 0.3620 inches single shaft and 0.3860 inches single shaft **Body Size:** 11 Stator Input Voltage Rating In Volts: 90.0 **Stator Input Current Rating:** 20.0 milliamperes **Stator Input Electrical Power Rating:** 270.0 milliwatts Frequency In Hertz: 400.0 **Zro Impedance Magnitude In Ohms:** Between 2672.00 and 4008.00 **Zro Impedance Angle In Deg:** Between 63.36 and 95.04 **Zso Impedance Magnitude In Ohms:** Between 4376.00 and 6564.00 Zso Impedance Angle In Deg:

Between 64.64 and 96.96

**Rotor Dc Resistance In Ohms:** 

Between 308.00 and 452.00

## NSN 5990-00-959-2373 Control Transformer Synchro - Page 2 of 2



Stator Dc Resistance In Ohms:
Between 444.00 and 666.00
Phase Shift Angle In Deg:
5.000 input to output
Maximum Fundamental Null Voltage In Millivolts Per Volt:
60.00 output
Maximum Total Null Voltage Output In Millivolts Per Volt:
100.00
Electrical Error Angular Range In Minutes:
-5.0/+5.0
Actuator Friction Torque At Minus 55 Deg Celsius:
16.0 centimeter-grams
Actuator Friction Torque At Plus 25 Deg Celsius:
4.0 centimeter-grams
Pilot Length:
Between 0.0590 inches and 0.0650 inches
Shoulder Length:
Between 0.0590 inches and 0.0650 inches
Mounting Surface To Terminal End Distance:
Between 1.7620 inches and 1.7680 inches
Terminal Location:
Rear
Shaft Slot Depth:
0.0300 inches single shaft
Shaft Slot Width:
0.0250 inches single shaft
Shaft Type:
Round, slotted single shaft
Transformation Ratio:
Between 0.698 rotor to stator and 0.772 rotor to stator
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A07800