

View Online at <https://aerobasegroup.com/nsn/5990-00-964-9672>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 1.3115 inches and 1.3120 inches

Pilot Diameter:

Between 0.8745 inches and 0.8750 inches

Overall Length:

2.4260 inches

Flange Diameter:

Between 1.4360 inches and 1.4370 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

1.3120 inches

Undercut Width:

0.0780 inches

Shaft Diameter:

0.1870 inches single shaft and 0.1872 inches single shaft

Shaft Length:

0.5400 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

15

Rotor Input Voltage Rating In Volts:

25.0

Frequency In Hertz:

5000.0

Rotor Dc Resistance In Ohms:

157.00

Stator Dc Resistance In Ohms:

92.00

Maximum Total Null Voltage Output In Millivolts Per Volt:

50.00

Electrical Error Angular Range In Minutes:

-10.0/+10.0

Spline Tooth Quantity:

21 single shaft

Actuator Friction Torque At Plus 25 Deg Celsius:

3.00 centimeter-grams

Alignment Hole Quantity:

4

Pilot Length:

0.0400 inches

Shoulder Length:

0.1320 inches

Mounting Surface To Terminal End Distance:

1.8000 inches

Spline Tooth Diametral Pitch:

120 single shaft

Shaft Thread Series Designator:

Unf single shaft

Shaft Thread Direction:

Right-hand single shaft

Shaft Thread Class:

2a single shaft

Terminal Location:

Rear

Shaft Thread Length:

0.2000 inches single shaft

Shaft Type:

Spline w/threads single shaft

Alignment Hole Depth:

0.1250 inches

Transformation Ratio:

0.811 stator to rotor

Alignment Hole Bolt Circle Diameter:

1.1000 inches

Shaft Thread Size:

0.132 inches single shaft

Terminal Type And Quantity:

8 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800