

View Online at <https://aerobasegroup.com/nsn/5990-00-965-9611>

**Body Material:**

Aluminum

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.8118 inches and 0.8123 inches

**Pilot Diameter:**

Between 0.4995 inches and 0.5000 inches

**Overall Length:**

1.5590 inches

**Flange Diameter:**

Between 0.9360 inches and 0.9370 inches

**Flange Thickness:**

0.0620 inches

**Undercut Diameter:**

Between 0.8370 inches and 0.8400 inches

**Undercut Width:**

0.0620 inches

**Shaft Diameter:**

0.0895 inches single shaft and 0.0900 inches single shaft

**Shaft Length:**

0.3190 inches single shaft

**Fragility Factor:**

Moderately rugged

**Body Size:**

10

**Rotor Input Voltage Rating In Volts:**

26.0

**Frequency In Hertz:**

400.0

**Rotor Input Current Rating:**

120.0 milliamperes

**Rotor Input Electrical Power Rating:**

600.0 milliwatts

**Zro Resistance In Ohms:**

37.00

**Zso Resistance In Ohms:**

11.00

**Zrs Resistance In Ohms:**

58.00

**Phase Shift Angle In Deg:**

4.000 input to output

**Torque Gradient Per Angular Deg:**

2350.000 millimeter-milligrams

**Pilot Length:**

0.0380 inches

**Shoulder Length:**

0.0630 inches

**Mounting Surface To Terminal End Distance:**

1.2400 inches

**Terminal Location:**

Rear

**Plus J Zro Reactance In Ohms:**

254.00

**Plus J Zso Reactance In Ohms:**

43.00

**Plus J Zrs Reactance In Ohms:**

23.00

**Shaft Type:**

Round single shaft

**Transformation Ratio:**

0.454 stator to rotor

**Terminal Type And Quantity:**

5 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A07800