

View Online at <https://aerobasegroup.com/nsn/5990-00-968-7400>

Body Material:

Aluminum

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

2.6900 inches

Flange Diameter:

Between 1.0610 inches and 1.0620 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches front shaft and 0.1200 inches front shaft

Shaft Length:

0.6250 inches front shaft

Body Size:

11

Stator Input Voltage Rating In Volts:

90.0

Stator Input Current Rating:

48.6 milliamperes

Stator Input Electrical Power Rating:

690.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

390.00

Zso Resistance In Ohms:

290.00

Rotor Dc Resistance In Ohms:

280.00

Stator Dc Resistance In Ohms:

190.00

Phase Shift Angle In Deg:

5.000 input to output

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.8350 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

1790.00

Shaft Slot Depth:

0.0300 inches rear shaft

Plus J Zso Reactance In Ohms:

1580.00

Shaft Slot Width:

0.0200 inches rear shaft

Shaft Type:

Round, slotted rear shaft

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800