

View Online at <https://aerobasegroup.com/nsn/5990-00-975-0559>

**Body Material:**

Steel, corrosion resisting

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.8118 inches and 0.8123 inches

**Pilot Diameter:**

Between 0.4995 inches and 0.5000 inches

**Overall Length:**

1.7860 inches

**Flange Diameter:**

Between 0.9360 inches and 0.9370 inches

**Flange Thickness:**

0.0630 inches

**Undercut Diameter:**

Between 0.8370 inches and 0.8400 inches

**Undercut Width:**

0.0620 inches

**Shaft Diameter:**

0.0880 inches single shaft and 0.0900 inches single shaft

**Shaft Length:**

0.3750 inches single shaft

**Body Size:**

10

**Stator Input Voltage Rating In Volts:**

11.8

**Stator Input Current Rating:**

21.0 milliamperes

**Stator Input Electrical Power Rating:**

50.0 milliwatts

**Frequency In Hertz:**

400.0

**Zro Resistance In Ohms:**

800.00

**Zso Resistance In Ohms:**

115.00

**Rotor Dc Resistance In Ohms:**

560.00

**Stator Dc Resistance In Ohms:**

100.00

**Phase Shift Angle In Deg:**

9.000 input to output

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

30.00

**Electrical Error Angular Range In Minutes:**

-7.5/+7.5

**Actuator Friction Torque At Minus 55 Deg Celsius:**

9.00 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

3.00 centimeter-grams

**Alignment Hole Quantity:**

3

**Pilot Length:**

0.0380 inches

**Shoulder Length:**

0.0620 inches

**Mounting Surface To Terminal End Distance:**

1.2410 inches

**Terminal Location:**

Rear

**Plus J Zro Reactance In Ohms:**

2900.00

**Shaft Slot Depth:**

0.0300 inches single shaft

**Plus J Zso Reactance In Ohms:**

470.00

**Shaft Slot Width:**

0.0200 inches single shaft

**Shaft Type:**

Round, slotted single shaft

**Alignment Hole Depth:**

0.0500 inches

**Transformation Ratio:**

0.501 rotor to stator

**Alignment Hole Bolt Circle Diameter:**

0.6780 inches

**Terminal Type And Quantity:**

5 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07800