

View Online at <https://aerobasegroup.com/nsn/5990-00-978-4936>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

2.3560 inches

Flange Diameter:

Between 1.0570 inches and 1.0620 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.1870 inches single shaft and 0.1872 inches single shaft

Shaft Length:

0.5620 inches single shaft

Maximum Temperature Rise:

25.0 degrees celsius

Body Size:

11

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

60.0 milliamperes

Rotor Input Electrical Power Rating:

1.0 watts

Zss Impedance Magnitude In Ohms:

Between 180.00 and 250.00

Zss Impedance Angle In Deg:

Between 20.00 and 28.00

Phase Shift Angle In Deg:

6.000 input to output

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Spline Tooth Quantity:

21 single shaft

Torque Gradient Per Angular Deg:

0.070 inch-ounces

Alignment Hole Quantity:

4

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7940 inches

Spline Tooth Diametral Pitch:

120 single shaft

Shaft Thread Series Designator:

Unf single shaft

Shaft Thread Direction:

Right-hand single shaft

Shaft Thread Class:

2a single shaft

Terminal Location:

Rear

Shaft Thread Length:

0.1970 inches single shaft

Shaft Type:

Spline w/threads single shaft

Alignment Hole Depth:

0.1250 inches

Transformation Ratio:

0.783 rotor to stator

Alignment Hole Bolt Circle Diameter:

0.8120 inches

Shaft Thread Size:

0.190 inches single shaft

Test Data Document:

81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

N/a

Fiig:

A07800