

View Online at <https://aerobasegroup.com/nsn/5990-00-982-8030>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

1.5620 inches

Pilot Diameter:

0.9375 inches

Overall Length:

3.1410 inches

Flange Diameter:

1.7500 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

1.6150 inches

Undercut Width:

0.0780 inches

Shaft Diameter:

0.1870 inches single shaft

Shaft Length:

0.5550 inches single shaft

Body Size:

18

Stator Input Voltage Rating In Volts:

90.0

Stator Input Current Rating:

70.0 milliamperes

Stator Input Electrical Power Rating:

2.0 watts

Frequency In Hertz:

60.0

Zso Impedance Magnitude In Ohms:

1875.00

Zso Impedance Angle In Deg:

75.00

Zrs Impedance Magnitude In Ohms:

1225.00

Zrs Impedance Angle In Deg:

18.00

Phase Shift Angle In Deg:

21.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

80.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

100.00

Electrical Error Angular Range In Minutes:

-8.0/+8.0

Spline Tooth Quantity:

21 single shaft

Actuator Friction Torque At Plus 25 Deg Celsius:

0.10 inch-ounces

Alignment Hole Quantity:

4

Pilot Length:

0.0400 inches

Shoulder Length:

0.1320 inches

Mounting Surface To Terminal End Distance:

2.5500 inches

Spline Tooth Diametral Pitch:

120 single shaft

Shaft Thread Series Designator:

Unf single shaft

Shaft Thread Direction:

Right-hand single shaft

Shaft Thread Class:

2a

Terminal Location:

Rear

Shaft Thread Length:

0.2000 inches single shaft

Shaft Type:

Spline w/threads single shaft

Alignment Hole Depth:

0.1250 inches

Transformation Ratio:

1.154 rotor to stator

Alignment Hole Bolt Circle Diameter:

1.0750 inches

Shaft Thread Size:

0.190 inches single shaft

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800