

View Online at <https://aerobasegroup.com/nsn/5990-00-988-6605>

**Body Material:**

Steel, stainless

**Body Style:**

Standard round a

**Pilot Diameter:**

Between 0.4995 inches and 0.5000 inches

**Overall Length:**

2.0240 inches

**Flange Diameter:**

0.7500 inches

**Flange Thickness:**

0.0620 inches

**Undercut Diameter:**

0.6900 inches

**Undercut Width:**

0.0620 inches

**Shaft Diameter:**

0.0895 inches single shaft and 0.0900 inches single shaft

**Shaft Length:**

0.4810 inches single shaft

**Body Size:**

8

**Stator Input Voltage Rating In Volts:**

11.8

**Stator Input Current Rating:**

22.0 milliamperes

**Stator Input Electrical Power Rating:**

58.0 milliwatts

**Frequency In Hertz:**

400.0

**Zro Resistance In Ohms:**

800.00

**Zso Resistance In Ohms:**

120.00

**Zrs Resistance In Ohms:**

920.00

**Rotor Dc Resistance In Ohms:**

550.00

**Stator Dc Resistance In Ohms:**

100.00

**Phase Shift Angle In Deg:**

9.200 input to output

**Maximum Fundamental Null Voltage In Millivolts Per Volt:**

0.02 output

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

0.03

**Electrical Error Angular Range In Minutes:**

-5.0/+5.0

**Actuator Friction Torque At Minus 55 Deg Celsius:**

9.00 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

3.00 centimeter-grams

**Pilot Length:**

0.0430 inches

**Mounting Surface To Terminal End Distance:**

1.3680 inches

**Terminal Location:**

Rear

**Plus J Zro Reactance In Ohms:**

2500.00

**Shaft Slot Depth:**

0.0250 inches single shaft

**Plus J Zso Reactance In Ohms:**

450.00

**Shaft Slot Width:**

0.0200 inches single shaft

**Plus J Zrs Reactance In Ohms:**

280.00

**Shaft Type:**

Round, slotted single shaft

**Transformation Ratio:**

0.454 rotor to stator

**Terminal Type And Quantity:**

5 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A07800