NSN 5990-00-988-6616

Receiver Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-988-6616

Body Material:
Steel, corrosion resisting
Body Style:
Standard round c
Shoulder Diameter:
Between 0.9995 inches and 1.0000 inches
Pilot Diameter:
Between 0.6245 inches and 0.6250 inches
Overall Length:
1.9750 inches
Flange Diameter:
Between 1.0610 inches and 1.0620 inches
Flange Thickness:
0.0930 inches
Undercut Diameter:
0.9750 inches
Undercut Width:
0.0500 inches
Shaft Diameter:
0.1195 inches single shaft and 0.1200 inches single shaft
Shaft Length:
0.3750 inches single shaft
Body Size:
11
Rotor Input Voltage Rating In Volts:
26.0
Frequency In Hertz:
400.0
Rotor Input Current Rating:
95.0 milliamperes
Rotor Input Electrical Power Rating:
370.0 milliwatts
Zro Resistance In Ohms:
42.00
Zso Resistance In Ohms:
10.00
Zrs Resistance In Ohms:
53.00
Rotor Dc Resistance In Ohms:
18.00
Stator Dc Resistance In Ohms:

7.50

NSN 5990-00-988-6616

Receiver Synchro - Page 2 of 2



Phase Shift Angle In Deg: 3.800 input to output **Electrical Error Angular Range In Minutes:** -15.0/+15.0 **Receiver Error Angular Range In Minutes:** -30.0/+30.0 **Actuator Friction Torque At Minus 55 Deg Celsius:** 5400.0 millimeter-milligrams **Actuator Friction Torque At Plus 25 Deg Celsius:** 2700.0 millimeter-milligrams **Torque Gradient Per Angular Deg:** 2400.0 millimeter-milligrams **Pilot Length:** 0.0620 inches **Shoulder Length:** 0.0620 inches **Mounting Surface To Terminal End Distance:** 1.6000 inches **Terminal Location:** Rear Plus J Zro Reactance In Ohms: 270.00 **Shaft Slot Depth:** 0.0220 inches single shaft and 0.0320 inches single shaft Plus J Zso Reactance In Ohms: 46.00 **Shaft Slot Width:** 0.0220 inches single shaft and 0.0320 inches single shaft Plus J Zrs Reactance In Ohms: 23.00 **Shaft Type:** Round, slotted single shaft **Transformation Ratio:** 0.453 rotor to stator **Terminal Type And Quantity:** 5 screw Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli

Fiig:

A07800