

View Online at <https://aerobasegroup.com/nsn/5990-00-990-8939>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

0.5000 inches

Overall Length:

1.9920 inches

Flange Diameter:

0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.6870 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.1200 inches single shaft

Shaft Length:

0.5840 inches single shaft

Body Size:

8

Stator Input Voltage Rating In Volts:

26.0

Stator Input Current Rating:

30.0 milliamperes

Stator Input Electrical Power Rating:

100.0 milliwatts

Frequency In Hertz:

400.0

Zro Impedance Magnitude In Ohms:

2570.00

Zro Impedance Angle In Deg:

73.00

Zso Impedance Magnitude In Ohms:

450.00

Zso Impedance Angle In Deg:

75.00

Zrs Impedance Magnitude In Ohms:

950.00

Zrs Impedance Angle In Deg:

20.00

Rotor Dc Resistance In Ohms:

350.00

Stator Dc Resistance In Ohms:

105.00

Maximum Fundamental Null Voltage In Millivolts Per Volt:

34.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

53.00

Actuator Friction Torque At Minus 55 Deg Celsius:

3.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

13.0 centimeter-grams

Pilot Length:

0.0400 inches

Mounting Surface To Terminal End Distance:

1.2410 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0310 inches single shaft

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

2.203 rotor to stator

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800