## NSN 5990-00-994-0555

Control Transformer Synchro - Page 1 of 2



·
View Online at https://aerobasegroup.com/nsn/5990-00-994-0555
Body Material:
Steel, corrosion resisting
Body Style:
Standard round a
Pilot Diameter:
Between 0.4995 inches and 0.5000 inches
Overall Length:
1.6150 inches
Flange Diameter:
Between 0.7490 inches and 0.7500 inches
Flange Thickness:
0.0620 inches
Undercut Diameter:
Between 0.6880 inches and 0.6910 inches
Undercut Width:
0.0620 inches
Shaft Diameter:
0.0895 inches single shaft and 0.0900 inches single shaft
Shaft Length:
0.3750 inches single shaft
Fragility Factor:
Moderately rugged
Body Size:
8
Stator Input Voltage Rating In Volts:
10.2
Stator Input Current Rating:
22.0 milliamperes
Stator Input Electrical Power Rating:
50.0 milliwatts
Frequency In Hertz:
400.0
Zro Resistance In Ohms:
650.00

Zso Resistance In Ohms:

105.00

**Zrs Resistance In Ohms:** 

810.00

**Rotor Dc Resistance In Ohms:** 

460.00

**Stator Dc Resistance In Ohms:** 

96.00

## NSN 5990-00-994-0555 Control Transformer Synchro - Page 2 of 2



Phase Shift Angle In Deg:
8.600 input to output
Maximum Total Null Voltage Output In Millivolts Per Volt:
30.00
Electrical Error Angular Range In Minutes:
-7.0/+7.0
Pilot Length:
0.0400 inches
Mounting Surface To Terminal End Distance:
1.2400 inches
Terminal Location:
Rear
Plus J Zro Reactance In Ohms:
2600.00
Plus J Zso Reactance In Ohms:
460.00
Plus J Zrs Reactance In Ohms:
260.00
Shaft Type:
Round single shaft
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A07800