

View Online at <https://aerobasegroup.com/nsn/5990-00-998-4306>

**Body Material:**

Steel, corrosion resisting

**Body Diameter:**

1.3820 mils and 1.3920 centimeters

**Fragility Factor:**

Moderately rugged

**Securing Hole Quantity:**

4

**Body Size:**

15

**Rotor Input Voltage Rating In Volts:**

115.0

**Frequency In Hertz:**

400.0

**Rotor Input Current Rating:**

67.0 milliamperes

**Rotor Input Electrical Power Rating:**

870.0 allqjaa3.500 finished-chamfered

**Zro Resistance In Ohms:**

195.00

**Zso Resistance In Ohms:**

180.00

**Zss Resistance In Ohms:**

330.00

**Rotor Dc Resistance In Ohms:**

100.00

**Stator Dc Resistance In Ohms:**

160.00

**Phase Shift Angle In Deg:**

3.200 input to output

**Maximum Fundamental Null Voltage In Millivolts Per Volt:**

75.00 output

**Electrical Error Angular Range In Minutes:**

-6.0/+6.0

**Mounting Surface To Terminal End Distance:**

1.6400 inches

**Mounting Facility Screw Thread Series Designator:**

Unc

**Terminal Location:**

Rear

**Plus J Zro Reactance In Ohms:**

1700.00

**Plus J Zso Reactance In Ohms:**

870.00

**Mounting Facility Screw Thread Diameter:**

0.125 inches

**Plus J Zss Reactance In Ohms:**

160.00

**Securing Hole Bolt Circle Diameter:**

2.3280 inches

**Special Features:**

Shaft modified with linear dial and knob installation

**Terminal Type And Quantity:**

5 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A07800