

View Online at <https://aerobasegroup.com/nsn/5990-01-016-9951>

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.8118 inches and 0.8123 inches

**Pilot Diameter:**

Between 0.4995 inches and 0.5000 inches

**Overall Length:**

1.9870 inches

**Flange Diameter:**

0.9370 inches

**Flange Thickness:**

0.0630 inches

**Undercut Diameter:**

Between 0.8400 inches and 0.8730 inches

**Undercut Width:**

0.0620 inches

**Shaft Diameter:**

0.0895 inches both shafts and 0.0900 inches both shafts

**Shaft Length:**

0.3750 inches both shafts

**Body Size:**

10

**Rotor Input Voltage Rating In Volts:**

115.0

**Frequency In Hertz:**

400.0

**Rotor Input Current Rating:**

33.0 milliamperes

**Rotor Input Electrical Power Rating:**

780.0 milliwatts

**Zro Resistance In Ohms:**

725.00

**Zso Resistance In Ohms:**

7.70

**Rotor Dc Resistance In Ohms:**

500.00

**Stator Dc Resistance In Ohms:**

7.30

**Phase Shift Angle In Deg:**

8.500 input to output

**Actuator Friction Torque At Plus 25 Deg Celsius:**

3.00 centimeter-grams

**Alignment Hole Quantity:**

3

**Pilot Length:**

0.0380 inches

**Shoulder Length:**

0.0620 inches

**Mounting Surface To Terminal End Distance:**

1.2410 inches

**Terminal Location:**

Side

**Plus J Zro Reactance In Ohms:**

3410.00

**Plus J Zso Reactance In Ohms:**

30.50

**Shaft Type:**

Round, slotted both shafts

**Alignment Hole Depth:**

0.0500 inches

**Alignment Hole Bolt Circle Diameter:**

0.6780 inches

**Terminal Type And Quantity:**

5 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07800