Control Transformer Synchro - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5990-01-030-0794

View Online at https://aerobasegroup.com/nsn/5990-01-030-0
Body Material:
Steel, corrosion resisting
Body Style:
Standard round c
Shoulder Diameter:
Between 0.9999 inches and 1.0000 inches
Pilot Diameter:
0.7500 inches
Overall Length:
Between 2.6130 inches and 2.6370 inches
Flange Diameter:
Between 1.0570 inches and 1.0600 inches
Flange Thickness:
Between 0.0900 inches and 0.0960 inches
Undercut Diameter:
Between 0.9995 inches and 1.0000 inches
Undercut Width:
0.0450 inches
Shaft Diameter:
0.1195 inches single shaft and 0.1200 inches single shaft
Shaft Length:
0.3200 inches single shaft and 0.3260 inches single shaft
Maximum Tempurature Rise:
8.0 degrees celsius
Body Size:
11
Stator Input Voltage Rating In Volts:
90.0
Stator Input Current Rating:
17.0 milliamperes
Stator Input Electrical Power Rating:
260.0 milliwatts
Frequency In Hertz:
400.0
Zro Resistance In Ohms:
437.00
Zso Resistance In Ohms:
265.00
Zrs Resistance In Ohms:
450.00
Rotor Dc Resistance In Ohms:
Between 327.25 and 442.75



Stator Dc Resistance In Ohms:
Between 185.25 and 204.75
Phase Shift Angle In Deg:
4.700 input to output
Maximum Fundamental Null Voltage In Millivolts Per Volt:
59.00 output
Maximum Total Null Voltage Output In Millivolts Per Volt:
94.00
Electrical Error Angular Range In Minutes:
-7.0/+7.0
Actuator Friction Torque At Minus 55 Deg Celsius:
16.0 centimeter-grams
Actuator Friction Torque At Plus 25 Deg Celsius:
4.0 centimeter-grams
Pilot Length:
0.0650 inches
Shoulder Length:
Between 0.0590 inches and 0.0650 inches
Mounting Surface To Terminal End Distance:
1.8120 inches
Terminal Location:
Rear
Plus J Zro Reactance In Ohms:
1940.00
Shaft Slot Depth:
0.0350 inches single shaft
Plus J Zso Reactance In Ohms:
Plus J Zso Reactance In Ohms: 1620.00
1620.00 Shaft Slot Width:
1620.00
1620.00 Shaft Slot Width: 0.0300 inches single shaft Plus J Zrs Reactance In Ohms:
1620.00 Shaft Slot Width: 0.0300 inches single shaft Plus J Zrs Reactance In Ohms: 222.00
1620.00 Shaft Slot Width: 0.0300 inches single shaft Plus J Zrs Reactance In Ohms: 222.00 Shaft Type:
1620.00 Shaft Slot Width: 0.0300 inches single shaft Plus J Zrs Reactance In Ohms: 222.00 Shaft Type: Round, slotted single shaft
1620.00 Shaft Slot Width: 0.0300 inches single shaft Plus J Zrs Reactance In Ohms: 222.00 Shaft Type: Round, slotted single shaft Transformation Ratio:
1620.00 Shaft Slot Width: 0.0300 inches single shaft Plus J Zrs Reactance In Ohms: 222.00 Shaft Type: Round, slotted single shaft Transformation Ratio: Between 1.108 rotor to stator and 1.200 rotor to stator
<ul> <li>1620.00</li> <li>Shaft Slot Width:</li> <li>0.0300 inches single shaft</li> <li>Plus J Zrs Reactance In Ohms:</li> <li>222.00</li> <li>Shaft Type:</li> <li>Round, slotted single shaft</li> <li>Transformation Ratio:</li> <li>Between 1.108 rotor to stator and 1.200 rotor to stator</li> <li>Terminal Type And Quantity:</li> </ul>
<ul> <li>1620.00</li> <li>Shaft Slot Width:</li> <li>0.0300 inches single shaft</li> <li>Plus J Zrs Reactance In Ohms:</li> <li>222.00</li> <li>Shaft Type:</li> <li>Round, slotted single shaft</li> <li>Transformation Ratio:</li> <li>Between 1.108 rotor to stator and 1.200 rotor to stator</li> <li>Terminal Type And Quantity:</li> <li>5 wire lead</li> </ul>
<ul> <li>1620.00</li> <li>Shaft Slot Width:</li> <li>0.0300 inches single shaft</li> <li>Plus J Zrs Reactance In Ohms:</li> <li>222.00</li> <li>Shaft Type:</li> <li>Round, slotted single shaft</li> <li>Transformation Ratio:</li> <li>Between 1.108 rotor to stator and 1.200 rotor to stator</li> <li>Terminal Type And Quantity:</li> <li>5 wire lead</li> <li>Shelf Life:</li> </ul>
<ul> <li>1620.00</li> <li>Shaft Slot Width:</li> <li>0.0300 inches single shaft</li> <li>Plus J Zrs Reactance In Ohms:</li> <li>222.00</li> <li>Shaft Type:</li> <li>Round, slotted single shaft</li> <li>Transformation Ratio:</li> <li>Between 1.108 rotor to stator and 1.200 rotor to stator</li> <li>Terminal Type And Quantity:</li> <li>5 wire lead</li> <li>Shelf Life:</li> <li>N/a</li> </ul>
<ul> <li>1620.00</li> <li>Shaft Slot Width:</li> <li>0.0300 inches single shaft</li> <li>Plus J Zrs Reactance In Ohms:</li> <li>222.00</li> <li>Shaft Type:</li> <li>Round, slotted single shaft</li> <li>Transformation Ratio:</li> <li>Between 1.108 rotor to stator and 1.200 rotor to stator</li> <li>Terminal Type And Quantity:</li> <li>5 wire lead</li> <li>Shelf Life:</li> </ul>
1620.00 Shaft Slot Width: 0.0300 inches single shaft Plus J Zrs Reactance In Ohms: 222.00 Shaft Type: Round, slotted single shaft Transformation Ratio: Between 1.108 rotor to stator and 1.200 rotor to stator Terminal Type And Quantity: 5 wire lead Shelf Life: N/a Unit Of Measure:
<ul> <li>1620.00</li> <li>Shaft Slot Width:</li> <li>0.0300 inches single shaft</li> <li>Plus J Zrs Reactance In Ohms:</li> <li>222.00</li> <li>Shaft Type:</li> <li>Round, slotted single shaft</li> <li>Transformation Ratio:</li> <li>Between 1.108 rotor to stator and 1.200 rotor to stator</li> <li>Terminal Type And Quantity:</li> <li>5 wire lead</li> <li>Shelf Life:</li> <li>N/a</li> </ul>

## NSN 5990-01-030-0794 Control Transformer Synchro - Page 3 of 3

Fiig: A07800

