

View Online at <https://aerobasegroup.com/nsn/5990-01-034-6717>

Body Material:

Aluminum alloy

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6500 inches

Flange Diameter:

Between 0.7470 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.6880 inches and 0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0900 inches single shaft

Shaft Length:

0.4000 inches single shaft

Body Size:

8

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

20.0 milliamperes

Rotor Input Electrical Power Rating:

105.0 milliwatts

Zro Resistance In Ohms:

400.00

Zso Resistance In Ohms:

300.00

Rotor Dc Resistance In Ohms:

315.00

Stator Dc Resistance In Ohms:

210.00

Phase Shift Angle In Deg:

11.500 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

35.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Pilot Length:

Between 0.0380 inches and 0.0430 inches

Mounting Surface To Terminal End Distance:

1.2400 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

1550.00

Shaft Slot Depth:

0.0300 inches single shaft

Plus J Zso Reactance In Ohms:

1250.00

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.846 stator to rotor

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800