

View Online at <https://aerobasegroup.com/nsn/5990-01-035-6869>

**Body Material:**

Aluminum alloy

**Body Style:**

Standard round a

**Pilot Diameter:**

Between 0.4995 inches and 0.5000 inches

**Overall Length:**

1.7500 inches

**Flange Diameter:**

Between 0.7470 inches and 0.7500 inches

**Flange Thickness:**

0.0620 inches

**Undercut Diameter:**

Between 0.6880 inches and 0.6910 inches

**Undercut Width:**

0.0620 inches

**Shaft Diameter:**

0.0900 inches single shaft

**Shaft Length:**

0.5000 inches single shaft

**Fragility Factor:**

Moderately rugged

**Body Size:**

8

**Rotor Input Voltage Rating In Volts:**

26.0

**Frequency In Hertz:**

400.0

**Rotor Input Current Rating:**

20.0 milliamperes

**Rotor Input Electrical Power Rating:**

105.0 milliwatts

**Zro Resistance In Ohms:**

400.00

**Zso Resistance In Ohms:**

300.00

**Rotor Dc Resistance In Ohms:**

315.00

**Stator Dc Resistance In Ohms:**

210.00

**Phase Shift Angle In Deg:**

11.500 input to output

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

35.00

**Electrical Error Angular Range In Minutes:**

-7.0 to 7.0

**Actuator Friction Torque At Plus 25 Deg Celsius:**

3.0 centimeter-grams

**Pilot Length:**

Between 0.0380 inches and 0.0430 inches

**Mounting Surface To Terminal End Distance:**

1.2400 inches

**Terminal Location:**

Rear

**Plus J Zro Reactance In Ohms:**

1550.00

**Shaft Slot Depth:**

0.0300 inches single shaft

**Plus J Zso Reactance In Ohms:**

1250.00

**Shaft Slot Width:**

0.0250 inches single shaft

**Shaft Type:**

Round, slotted single shaft

**Transformation Ratio:**

0.846 stator to rotor

**Terminal Type And Quantity:**

7 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A07800