

View Online at <https://aerobasegroup.com/nsn/5990-01-084-0807>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

0.5000 inches

Overall Length:

2.0780 inches

Flange Diameter:

0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.7470 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0900 inches single shaft

Shaft Length:

0.5000 inches single shaft

Body Size:

8

Stator Input Voltage Rating In Volts:

13.0

Stator Input Current Rating:

17.0 milliamperes

Stator Input Electrical Power Rating:

60.0 milliwatts

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

10.0 milliamperes

Rotor Input Electrical Power Rating:

91.6 milliwatts

Zro Resistance In Ohms:

916.00

Zso Resistance In Ohms:

206.00

Zrs Resistance In Ohms:

990.00

Rotor Dc Resistance In Ohms:

725.00

Stator Dc Resistance In Ohms:

160.00

Phase Shift Angle In Deg:

17.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

30.00 input

Maximum Total Null Voltage Output In Millivolts Per Volt:

75.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

0.0430 inches

Mounting Surface To Terminal End Distance:

1.5630 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

2430.00

Shaft Slot Depth:

0.0350 inches single shaft

Plus J Zso Reactance In Ohms:

737.00

Shaft Slot Width:

0.0250 inches single shaft

Plus J Zrs Reactance In Ohms:

440.00

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.485 rotor to stator

Terminal Type And Quantity:

5 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800