

View Online at <https://aerobasegroup.com/nsn/5990-01-174-4469>

Body Material:

Any acceptable

Body Style:

Standard round a

Pilot Diameter:

0.5000 inches

Overall Length:

1.6180 inches

Flange Diameter:

0.7550 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.6900 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.9000 inches single shaft

Shaft Length:

0.3150 inches single shaft

Body Size:

8

Rotor Input Voltage Rating In Volts:

7.1

Frequency In Hertz:

400.0

Rotor Input Current Rating:

17.0 milliamperes

Rotor Input Electrical Power Rating:

500.0 milliwatts

Zro Resistance In Ohms:

149.00

Zso Resistance In Ohms:

30.20

Rotor Dc Resistance In Ohms:

120.00

Stator Dc Resistance In Ohms:

22.70

Phase Shift Angle In Deg:

10.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

4.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

6.00

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

0.0400 inches

Mounting Surface To Terminal End Distance:

1.2400 inches

Shaft Maximum Runout:

0.0010 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

558.00

Shaft Slot Depth:

0.0300 inches single shaft

Plus J Zso Reactance In Ohms:

137.00

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.454 rotor to stator

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A07800