

View Online at <https://aerobasegroup.com/nsn/5990-01-247-7411>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round b

Shoulder Diameter:

1.3120 inches

Pilot Diameter:

0.5000 inches

Overall Length:

2.1310 inches

Flange Diameter:

1.4370 inches

Flange Thickness:

0.0930 inches

Undercut Width:

0.0780 inches

Shaft Diameter:

0.1200 inches single shaft

Shaft Length:

0.5000 inches single shaft

Body Size:

15

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

113.0 milliamperes

Rotor Input Electrical Power Rating:

480.0 milliwatts

Zro Resistance In Ohms:

45.80

Zso Resistance In Ohms:

10.70

Zrs Resistance In Ohms:

43.50

Rotor Dc Resistance In Ohms:

16.00

Stator Dc Resistance In Ohms:

7.00

Phase Shift Angle In Deg:

3.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Receiver Error Angular Range In Minutes:

-6.0/+6.0

Actuator Friction Torque At Minus 55 Deg Celsius:

2.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

5.0 centimeter-grams

Torque Gradient Per Angular Deg:

2250.0 millimeter-milligrams

Pilot Length:

0.0400 inches

Shoulder Length:

0.1320 inches

Mounting Surface To Terminal End Distance:

1.5910 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

241.00

Shaft Slot Depth:

0.0310 inches single shaft

Plus J Zso Reactance In Ohms:

42.00

Shaft Slot Width:

0.0310 inches single shaft

Plus J Zrs Reactance In Ohms:

27.60

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800