

View Online at <https://aerobasegroup.com/nsn/5990-01-311-4762>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

1.9910 inches

Flange Diameter:

Between 1.0610 inches and 1.0620 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3130 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

11

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

56.0 milliamperes

Rotor Input Electrical Power Rating:

895.0 allqjaa3.500 finished-chamfered

Zro Resistance In Ohms:

285.00

Zso Resistance In Ohms:

200.00

Rotor Dc Resistance In Ohms:

160.00

Stator Dc Resistance In Ohms:

175.00

Phase Shift Angle In Deg:

4.500 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

100.00 output

Actuator Friction Torque At Minus 55 Deg Celsius:

9.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Shaft Maximum Radial Play:

0.0008 inches

Shaft End Play:

Between 0.0005 inches and 0.0015 inches

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.6000 inches

Shaft Maximum Runout:

0.0010 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

2000.00

Shaft Slot Depth:

0.0220 inches single shaft and 0.0320 inches single shaft

Plus J Zso Reactance In Ohms:

1020.00

Shaft Slot Width:

0.0220 inches single shaft and 0.0320 inches single shaft

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800