NSN 5990-01-384-9747

Transmitter Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-01-384-9747

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

1.7240 inches

Flange Diameter:

Between 1.0610 inches and 1.0620 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3600 inches single shaft and 0.3900 inches single shaft

Maximum Tempurature Rise:

125.0 degrees celsius

Body Size:

11

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

45.0 milliamperes

Rotor Input Electrical Power Rating:

0.77 watts finished-chamfered

Zro Resistance In Ohms:

350.00

Zso Resistance In Ohms:

4.30

Zss Resistance In Ohms:

5.00

Rotor Dc Resistance In Ohms:

Between 170.00 and 220.00

NSN 5990-01-384-9747 Transmitter Synchro - Page 2 of 2



Stator Dc Resistance In Ohms:	
Between 3.20 and 4.00	
Maximum Fundamental Null Voltage In Millivolts Per Volt:	
30.00 input	
Shaft End Play:	
Between 0.0010 inches and 0.0025 inches	
Pilot Length:	
0.0590 mils and 0.0650 centimeters	
Shoulder Length:	
0.0590 mils and 0.0650 centimeters	
Mounting Surface To Terminal End Distance:	
1.6000 inches	
Shaft Maximum Runout:	
0.0010 inches	
Terminal Location:	
Rear	
Plus J Zro Reactance In Ohms:	
3000.00	
Plus J Zso Reactance In Ohms:	
24.60	
Shaft Type:	
Round single shaft	
Plus J Zss Reactance In Ohms:	
2.50	
Transformation Ratio:	
0.1026 rotor to stator	
Shaft End Play Determining Weight:	
8.5 ounces	
Special Features:	
Slot optional on shaft	
Terminal Type And Quantity:	
5 wire lead	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A07800	