NSN 5995-00-252-5849

-40.0 degrees celsius and 65.0 degrees celsius

Cross Sectional Shape:

Round

7.000 feet

N/a

Overall Length:

Tempurature Rating:

Electrical Power Cable Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5995-00-252-5849

| Cross Section Outside Diameter: |
|---------------------------------------------------------------------------------------------|
| 0.375 inches |
| Termination Type: |
| Connector receptacle both ends all conductors |
| Conductor Quantity: |
| 2 |
| Accessory Wire Type And Quantity: |
| 1 ground |
| Strand Quantity Per Conductor: |
| 41 all conductors |
| Conductor Form: |
| Stranded all conductors |
| Round Conductor Size: |
| 18 awg all conductors |
| Strand Awg Size Per Conductor: |
| 34 all conductors |
| Conductor Arrangement And Quantity: |
| 2 singles |
| Voltage Rating: |
| 600.0 ac rated working voltage all conductors |
| Terminal Manufacturer Identifying Reference Number: |
| Ms3116j-12-3s 2nd end all conductors |
| Terminal Commercial And Government Entity Code: |
| 96906 2nd end all conductors |
| Special Features: |
| Cable co-o2mof/2/18/sj0375 |
| Color: |
| White 1st position cover first conductor |
| Material: |
| Rubber chloroprene class cr 1st position jacket cable |
| Material Specification: |
| Qq-w-343, soft federal specification single material response core conductor all conductors |
| Style Designator: |
| Jack and external connector |
| Shelf Life: |
| N/o |

NSN 5995-00-252-5849

Electrical Power Cable Assembly - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

Yes - demil/mli

Fiig:

A077a0

Mil-std (military Standard):

Mil-i-3930 spec.