

View Online at https://aerobasegroup.com/nsn/5995-00-548-9569

Courd         Round         Overall Length:         20.833 fed         Electrical Resistance:         50.00 ohms impedance         Tempurature Rating:         -40.0 degrees celsius and 85.0 degrees celsius         Cross Section Outside Diameter:         0.870 inches         End Application:         Antm-6 radio set         Termination Type:         Conductor Pulp both ends single conductor         Conductor Quantity:         1         Conductor Form:         Solid single conductor         Solid single conductor         Round Conductor Size:         S ang single conductor         Conductor Size:         S ang single conductor         Solid single conductor         Solid Single conductor         Special Features:         Rg218 cable         Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Syle Designator:         Internal and external connector         Syle Designator:         Internal and external connector         Syle Designator:         Internal and external connector         Syle Designator:	Cross Sectional Shape:
Overall Length:         20.833 feet         Electrical Resistance:         50.00 ohms impedance         Tempurature Rating:         -40.0 degrees celsius and 85.0 degrees celsius         Cross Section Outside Diameter:         0.870 inches         End Application:         Antrn-6 radio set         Termination Type:         Conductor Quantity:         1         Conductor Form:         Solid single conductor         Round Conductor Size:         5 avg single conductor         Conductor Size:         5 avg single conductor         Conductor Size:         5 avg single conductor         Solid Single conductor         Conductor Arrangement And Quantity:         1 to avail         Terminat Commercial And Government Entity Code:         80058 both ends single conductor         Special Features:         Rg218 cable         Material         Postification         Caqw-34 I deteral specification single material response 2nd position shield braid, metallic single conductor         Syle Designator:         Internal and external connector         Syle Designator:         Iva         Material </td <td></td>	
20.833 fee         Electrical Resistance:         50.00 ohms impedance         Tempurature Rating:         -40.0 degrees celsius and 85.0 degrees celsius         Cross Section Outside Diameter:         0.870 inches         End Application:         Antrn-6 radio set         Termination Type:         Conductor Quantity:         1         Conductor Form:         Solid single conductor         Round Conductor Size:         5 awg single conductor         Conductor Arrangement And Quantity:         1 coaxial         Terminal Commercial And Government Entity Code:         80058 both ends single conductor         Sugs labe inductor         Material:         Placable         Material         Quev-Sid Ideation single material response 2nd position shield braid, metallic single conductor         Suple Signator:         Internal and external connector         Style Designator:         Na         Unit Of Measure:         Na         Desiliarization:         Via         Signator:         Feer         Na         Signator:         Signator: <td></td>	
Electrical Resistance:         50.00 ohms impedance         Fempurature Rating:         -40.0 degrees celsius and 85.0 degrees celsius         Corse Section Outside Diameter:         0.870 inches         End Application:         Andru-F radio set         Termination Type:         Connector plug both ends single conductor         Conductor Quantity:         1         Conductor Form:         Solid single conductor         Round Conductor Size:         5 avg single conductor         Conductor Arrangement And Quantity:         1 coaxial         Terminal Commercial And Government Entity Code:         80058 both ends single conductor         Solge I Features:         Rogal Features:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Style Designator:         Internal and external connector         Style Designator:         Internal and external connector         Style Designator:         Iva         Internal and external connector         Style Designator:         Iva         Internal and external connector         Style Designator:         Iva	-
50.00 ohms impedance Tempurature Rating: -40.0 degrees celsius and 85.0 degrees celsius Cross Section Outside Diameter: 0.870 inches End Application: Antm-6 radio set Termination Type: Connector plug both ends single conductor Conductor Quantity: 1 Conductor Quantity: 1 Conductor Form: Solid single conductor Conductor Size: 3 awg single conductor Conductor Arrangement And Quantity: 1 to axial Terminal Commercial And Government Entity Code: 80058 both ends single conductor Special Features: Rg218 cable Material: Plastic polyethylene terephthalate 1st position primary insulation single conductor Syle Designator: Naterial Specification Internal and external connector Syle Designator: Internal and external connector Shelf Life: Na Conductor Material Conductor Conductor Size: Conductor Special Features: Rg218 cable Material: Rg218 cable Rd218 cable Rd	
Tempurature Rating:         -40.0 degrees celsius and 85.0 degrees celsius         Cross Section Outside Diameter:         0.870 inches         End Application:         Andrn-6 radio set         Termination Type:         Connector plug both ends single conductor         Conductor Quantity:         1         Conductor Form:         Solid single conductor         Round Conductor Size:         5 awg single conductor         Conductor Arrangement And Quantity:         1 conductor Arrangement And Quantity:         1 solid single conductor         Boosal         Regreta cable         Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Superal Retures:         Ray: Ald federal specification single material response 2nd position shield braid, metallic single conductor         Shell If:         Via         Mutrici         Na         Mutrici         Na         Material connector         Shell If the:         Na         Mutrici         Na         Mutrici         Na         Dit Of Measure:	
-40.0 degrees celsius and 85.0 degrees celsius Cross Section Outside Diameter: 0.870 inches End Application: An/tm-6 radio set Termination Type: Connector plug both ends single conductor Conductor Quantity: 1 Conductor Guantity: 1 Conductor Form: Solid single conductor Round Conductor Size: 5 awg single conductor Conductor Arrangement And Quantity: 1 coaxial Terminal Commercial And Government Entity Code: 80058 both ends single conductor Special Features: Rg218 cable Material: Plastic polyethylene terephthalate 1st position primary insulation single conductor Syle Designator: Arterial and external connector Syle Designator: Internal and external connector Sheff Life: Na Unit Of Measure: - Features: Rg2 - Admit/Mii Fig:	
Cross Section Outside Diameter:         0.870 inches         End Application:         Antrn-6 radio set         Termination Type:         Connector plug both ends single conductor         Conductor Quantity:         1         Conductor Form:         Solid single conductor         Round Conductor Size:         5 awg single conductor         Conductor Arrangement And Quantity:         1 coaxial         Terminal Commercial And Government Entity Code:         80058 both ends single conductor         Special Features:         Rg218 cable         Material:         Pastic polyethylene terephthalate 1st position primary insulation single conductor         Syle Designator:         Nava 343 federal specification single material response 2nd position shield braid, metallic single conductor         Syle Designator:         Nava 343 federal specification single material response 2nd position shield braid, metallic single conductor         Syle Diffication:         Nava         Choff Measure:         Nava         File If if:         Nava         File If	
0.870 inches         End Application:         An/trn-6 radio set         Termination Type:         Connector plug both ends single conductor         Conductor Quantity:         1         Conductor Form:         Solid single conductor         Round Conductor Size:         5 awg single conductor         Conductor Arrangement And Quantity:         1 coaxial         Terminal Commercial And Government Entity Code:         80058 both ends single conductor         Special Features:         Rg218 cable         Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Guq-w-343 federal specification single material response 2nd position shield braid, metallic single conductor         SyleD Goignator:         Internal and external connector         Shelf Life:         N/a         Unit Of Measure:         -         Demilitarization:         Yes - demil/mli         Fig:	
End Application:         An/tm-6 radio set         Termination Type:         Connector plug both ends single conductor         Conductor Quantity:         1         Conductor Form:         Solid single conductor         Round Conductor Size:         5 awg single conductor         Conductor Arrangement And Quantity:         1 coaxial         Terminal Commercial And Government Entity Code:         80058 both ends single conductor         Special Features:         Rg218 cable         Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Syle Designator:         Internal and external connector         Syle Designator:         Internal and external connector         Shelf Life:         N/a         Unit Of Measure:         -         Demilitarization:         Yes - demil/mli	
An/tm-B radio set         Fermination Type:         Connector plug both ends single conductor         Conductor Quantity:         1         Conductor Form:         Solid single conductor         Round Conductor Size:         5 avg single conductor         Conductor Arrangement And Quantity:         1 coaxial         Terminal Commercial And Government Entity Code:         80058 both ends single conductor         Special Features:         Rg218 cable         Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Syle Designator:         Naterial Specification:         Naterial and external connector         Syle Designator:         Internal and external connector         Shelf Life:         N/a         Lift Of Measure:         -         Demiliarization:         Yes - demil/mli	
Fermination Type:Connector plug both ends single conductorConductor Quantity:1Conductor Form:Solid single conductorFound Conductor Size:5 avg single conductorConductor Arrangement And Quantity:1 coaxialTerminal Commercial And Government Entity Code:80058 both ends single conductorSpecial Features:Rg218 cableMaterial:Plastic polyethylene terephthalate 1st position primary insulation single conductorSyle Designator:Syle Designator:Naterial and external connectorSheft Life:N/aInternal and external connectorSheft Life:N/aSheft Life:N/aSub Conductor:Single ConductorSheft Life:N/aSheft Life:N/aSub Conductor:Single Conductor:Single ConductorSingle Con	
Conector plug both ends single conductor Conductor Quantity: 1 Conductor Form: Solid single conductor Round Conductor Size: 3 awg single conductor Conductor Arrangement And Quantity: 1 coaxial Terminal Commercial And Government Entity Code: 80058 both ends single conductor Special Features: Rg218 cable Material: Plastic polyethylene terephthalate 1st position primary insulation single conductor Material Specification Graw-343 federal specification single material response 2nd position shield braid, metallic single conductor Syle Designator: Naterial and external connector Shift Life: Na Material: M	
Conductor Quantity:         1         Conductor Form:         Solid single conductor         Round Conductor Size:         5 awg single conductor         Conductor Arrangement And Quantity:         1 coaxial         Terninal Commercial And Government Entity Code:         80058 both ends single conductor         Special Features:         Rg218 cable         Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Material Specification:         Qr-w-343 federal specification single material response 2nd position shield braid, metallic single conductor         Shift Life:         N/a         Unt Of Measure:         -         millanization:         Yes - demil/mli         Fig:	
1         Conductor Form:         Solid single conductor         Round Conductor Size:         5 awg single conductor         Conductor Arangement And Quantity:         Conductor Arangement And Quantity:         1 coaxial         Terninal Commercial And Government Entity Code:         80058 both ends single conductor         Special Features:         Rg218 cable         Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Material         Qav-343 federal specification single material response 2nd position shield braid, metallic single conductor         Shelf Life:         Na         Internal and external connector         Shelf Life:         Na         Dird Measure:         -         femilitarization:         Formilitarization:         Formilitarization:	
Conductor Form:         Solid single conductor         Round Conductor Size:         5 awg single conductor         2 awg single conductor         Conductor Arrangement And Quantity:         1 coaxial         Terminal Commercial And Government Entity Code:         80058 both ends single conductor         Special Features:         Rg218 cable         Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Material Specification:         Qq-w-343 federal specification single material response 2nd position shield braid, metallic single conductor         Shelf Life:         N/a         Unter Maesure:         Iva         Va         Fig:	
Solid single conductor         Round Conductor Size:         3 way single conductor         Gonductor Arrangement And Quantity:         1 coaxial         Terminal Commercial And Government Entity Code:         80058 both ends single conductor         Special Features:         Rg218 cable         Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Material Specification:         Q-qw-343 federal specification single material response 2nd position shield braid, metallic single conductor         Shelf Life:         N/a         Internal and external connector         Shelf Life:         N/a         Guitt of Measure:	
Round Conductor Size:         5 awg single conductor         Conductor Arrangement And Quantity:         1 coaxial         Terminal Commercial And Government Entity Code:         80058 both ends single conductor         Special Features:         Rg218 cable         Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Material Specification:         Qq-w-343 federal specification single material response 2nd position shield braid, metallic single conductor         Style Designator:         Internal and external connector         Shelf Life:         N/a         Unit Of Measure:         -         Yes - demil/mli         Fig:	
S awg single conductor         Conductor Arrangement And Quantity:         1 coaxial         Terminal Commercial And Government Entity Code:         80058 both ends single conductor         Special Features:         Rg218 cable         Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Material Specification:         Qr-w-343 federal specification single material response 2nd position shield braid, metallic single conductor         Style Designator:         Internal and external connector         Sheff Life:         Iva         Tori Of Measure:            Partitizzation:         Tremiltarization:         Fremiltarization:         Fig:	
Conductor Arrangement And Quantity: 1 coaxial Terminal Commercial And Government Entity Code: 80058 both ends single conductor Special Features: Rg218 cable Material Plastic polyethylene terephthalate 1st position primary insulation single conductor Material Specification: Qq-w-343 federal specification single material response 2nd position shield braid, metallic single conductor Style Designator: Internal and external connector Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
1 coaxial Terminal Commercial And Government Entity Code: 80058 both ends single conductor Special Features: Rg218 cable Rdaterial: Plastic polyethylene terephthalate 1st position primary insulation single conductor Material Specification: Qq-w-343 federal specification single material response 2nd position shield braid, metallic single conductor Style Designator: Internal and external connector Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Terminal Commercial And Government Entity Code:         80058 both ends single conductor         Special Features:         Rg218 cable         Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Material Specification:         Qq-w-343 federal specification single material response 2nd position shield braid, metallic single conductor         Style Designator:         Internal and external connector         Shelf Life:         N/a         Unit Of Measure:         -         Penilitarization:         Yes - demil/mli         Fig:	
80058 both ends single conductorSpecial Features:Rg218 cableMaterial:Plastic polyethylene terephthalate 1st position primary insulation single conductorMaterial Specification:Qq-w-343 federal specification single material response 2nd position shield braid, metallic single conductorStyle Designator:Internal and external connectorShelf Life:N/aUnit Of Measure:-Specification:Yes - demil/mliFig:	
Special Features:         Rg218 cable         Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Material Specification:         Qq-w-343 federal specification single material response 2nd position shield braid, metallic single conductor         Style Designator:         Internal and external connector         Shelf Life:         N/a         Dunit Of Measure:            Jenilitarization:         Yes - demil/mli         Fig:	
Rg218 cable         Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Material Specification:         Qq-w-343 federal specification single material response 2nd position shield braid, metallic single conductor         Style Designator:         Internal and external connector         Shelf Life:         N/a         Unit Of Measure:            Pemilitarization:         Yes - demil/mli         Fig:	
Material:         Plastic polyethylene terephthalate 1st position primary insulation single conductor         Material Specification:         Qq-w-343 federal specification single material response 2nd position shield braid, metallic single conductor         Style Designator:         Internal and external connector         Shelf Life:         N/a         Unit Of Measure:            Specification:         Yes - demil/mli         Fig:	-
Plastic polyethylene terephthalate 1st position primary insulation single conductor Material Specification: Qq-w-343 federal specification single material response 2nd position shield braid, metallic single conductor Style Designator: Internal and external connector Shelf Life: N/a Vnit Of Measure: Demilitarization: Yes - demil/mli Fiig:	-
Material Specification:         Qq-w-343 federal specification single material response 2nd position shield braid, metallic single conductor         Style Designator:         Internal and external connector         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         Yes - demil/mli         Fig:	
Qq-w-343 federal specification single material response 2nd position shield braid, metallic single conductor   Style Designator:   Internal and external connector   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   Yes - demil/mli   Fiig:	
Style Designator: Internal and external connector Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Filg:	
Internal and external connector Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   Yes - demil/mli   Fiig:	
N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Filg:	
Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	
 Demilitarization: Yes - demil/mli Fiig:	
Yes - demil/mli Fiig:	
Yes - demil/mli Fiig:	Demilitarization:
Fiig:	
-	
	-