## NSN 5995-00-564-9867

Electrical Power Cable Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5995-00-564-9867

| View Online at https://aerobasegroup.com/nsn/5995-00-564-9867                               |
|---|
| Cross Sectional Shape:  |
| Round   |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit and 160.0 degrees fahrenheit                                       |
| Cross Section Outside Diameter:   |
| 1.230 inches  |
| Termination Type:   |
| Connector plug both ends all conductors   |
| Conductor Quantity:   |
| 24  |
| Accessory Wire Type And Quantity:   |
| 72 reinforcement  |
| Color Coding Document:  |
| 8171827-18876 drawing   |
| Strand Quantity Per Conductor:  |
| 16 all conductors   |
| Conductor Form:   |
| Stranded all conductors   |
| Round Conductor Size:   |
| 18 awg all conductors   |
| Strand Awg Size Per Conductor:  |
| 30 all conductors   |
| Voltage Rating:   |
| 600.0 root mean square (rms) operating voltage all conductors                               |
| Terminal Manufacturer Identifying Reference Number:   |
| 8171832 2nd end all conductors  |
| Terminal Commercial And Government Entity Code:   |
| 18876 2nd end all conductors  |
| Material:   |
| Plastic polyamide 1st position jacket cable   |
| Material Specification:   |
| Qq-w-343, soft federal specification single material response core conductor all conductors |
| Surface Treatment:  |
| Tin core conductor all conductors   |
| Style Designator:   |
| Jack and external connector   |
| Fsc Application Data:   |
| Missile guidance central  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5995-00-564-9867

Electrical Power Cable Assembly - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

No

Fiig:

A077a0

Mil-std (military Standard):

Mil-m-20693 spec.