Electrical Power Cable Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5995-00-889-1148

Cross Sectional Shape: Round Overall Length: 8.000 feet Tempurature Rating: -40.0 degrees celsius and 65.0 degrees celsius Cross Section Outside Diameter: 0.500 inches Termination Type: Connector plug 1st end all conductors
Overall Length: 8.000 feet Tempurature Rating: -40.0 degrees celsius and 65.0 degrees celsius Cross Section Outside Diameter: 0.500 inches Termination Type:
8.000 feet Tempurature Rating: -40.0 degrees celsius and 65.0 degrees celsius Cross Section Outside Diameter: 0.500 inches Termination Type:
Tempurature Rating: -40.0 degrees celsius and 65.0 degrees celsius Cross Section Outside Diameter: 0.500 inches Termination Type:
-40.0 degrees celsius and 65.0 degrees celsius Cross Section Outside Diameter: 0.500 inches Termination Type:
Cross Section Outside Diameter: 0.500 inches Termination Type:
0.500 inches Termination Type:
Termination Type:
Connector plug 1st end all conductors
Conductor Quantity:
4
Strand Quantity Per Conductor:
41 all conductors
Conductor Form:
Stranded all conductors
Round Conductor Size:
14 awg all conductors
Strand Awg Size Per Conductor:
30 all conductors
Conductor Arrangement And Quantity:
2 singles
Voltage Rating:
600.0 ac rated working voltage all conductors
Terminal Manufacturer Identifying Reference Number:
Mw10 (m) a17 1st end all conductors
Terminal Commercial And Government Entity Code:
81349 1st end all conductors
Individual Conductor Length:
6.000 inches 2nd end all conductors
Special Features:
Cable, jetds, cx 4720 vrc
Material:
Rubber chloroprene class cr 1st position jacket cable
Material Specification:
Qq-w-343, soft federal specification single material response core conductor all conductors
Style Designator:
Stripped
Shelf Life:
N/a
Unit Of Measure:
-



Demilitarization:

Yes - demil/mli

Fiig:

A077a0

Mil-std (military Standard):

Mil-i-3930 spec.