NSN 5995-00-927-4275

Electrical Lead - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5995-00-927-4275

Cross Section Outside Diameter: 0.105 inches Leadlength: 17.156 inches Strand Quantity Per Conductor: 19 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 16 awg single conductor Stranded single conductor Stranded single conductor Stranded single conductor Stranded single conductor Strand was Size Per Conductor: 29 single conductor Voltage Rating: 600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A077a0	
Cross Section Outside Diameter: 0.105 inches Leadlength: 17.156 inches Strand Quantity Per Conductor: 19 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 16 awg single conductor Strand Awg Size Per Conductor: 29 single conductor Voltage Rating: 600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material: Tin core conductor single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Cross Sectional Shape:
0.105 inches Leadlength: 17.156 inches Strand Quantity Per Conductor: 19 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 16 awg single conductor Strand Awg Size Per Conductor: 29 single conductor Strand Awg Size Per Conductor: 29 single conductor Voltage Rating: 600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Leadlength: 17.156 inches Strand Quantity Per Conductor: 19 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 16 awg single conductor Strand Awg Size Per Conductor: 29 single conductor Voltage Rating: 600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Strand Quantity Per Conductor: 19 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 16 awg single conductor Strand Awg Size Per Conductor: 29 single conductor Voltage Rating: 600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Ses Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Strand Quantity Per Conductor: 19 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 16 awg single conductor Strand Awg Size Per Conductor: 29 single conductor Voltage Rating: 600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Leadlength:
19 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 16 awg single conductor Strand Awg Size Per Conductor: 29 single conductor Voltage Rating: 600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	17.156 inches
Conductor Form: Stranded single conductor Round Conductor Size: 16 awg single conductor Strand Awg Size Per Conductor: 29 single conductor Voltage Rating: 600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Strand Quantity Per Conductor:
Stranded single conductor Round Conductor Size: 16 awg single conductor Strand Awg Size Per Conductor: 29 single conductor Voltage Rating: 600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	19 single conductor
Round Conductor Size: 16 awg single conductor Strand Awg Size Per Conductor: 29 single conductor Voltage Rating: 600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Conductor Form:
16 awg single conductor Strand Awg Size Per Conductor: 29 single conductor Voltage Rating: 600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Stranded single conductor
Strand Awg Size Per Conductor: 29 single conductor Voltage Rating: 600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Round Conductor Size:
29 single conductor Voltage Rating: 600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	16 awg single conductor
Voltage Rating: 600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wirring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Strand Awg Size Per Conductor:
600.0 ac rated working voltage single conductor Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	29 single conductor
Terminal Lug Aperture Size: 0.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Voltage Rating:
O.147 inches 1st end single conductor Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	600.0 ac rated working voltage single conductor
Terminal Manufacturer Identifying Reference Number: Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Lug Aperture Size:
Ms25036-107 1st end single conductor Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.147 inches 1st end single conductor
Terminal Commercial And Government Entity Code: 96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Manufacturer Identifying Reference Number:
96906 1st end single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ms25036-107 1st end single conductor
Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Commercial And Government Entity Code:
Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	96906 1st end single conductor
Material Specification: Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Plastic polyvinyl chloride 1st position primary insulation single conductor
Surface Treatment: Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material Specification:
Tin core conductor single conductor Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Mil-y-1140 military specification single material response 2nd position braid, non-metallic single conductor
Fsc Application Data: Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
Vehicular wiring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tin core conductor single conductor
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Fsc Application Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	Vehicular wiring
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A077a0	Fiig:
	A077a0
Mil-std (military Standard):	Mil-std (military Standard):

Mil-m-20693 spec.