

View Online at <https://aerobasegroup.com/nsn/5995-01-042-5322>

**Special Features:**

Cable specification data: mil-c-13777, usaecom dwg sc-d-866286, sc-d-866293; conductor data: branches (br)a, b, d neoprene jacket covering, 0.397 in. O/a dia, 600 vdc, 11 conductors, copper, stranded, no. 22 awp with fep; insulation shield data: 2 conductors covered by separate shield, 11 conductors covered by shield; br c polyvinyl jacket covering, 0.250 in. O/a dia, 600 vdc, 4 conductors, copper, stranded, no. 22 awg; shield data: 2 conductors covered by separate shield, 4 conductors covered by shield; dimensional data: br a, 12 in. From molded crotch; br b, 4 ft. From molded crotch; br c, 11 in. From molded crotch; br d, 5 in. From molded tip; terminal data: br a, plug, electrical, burndy corp. P/n bt06a-12-10p, 1 ea; br b, plug, electrical, burndy corp. P/n bt06a-16-26s, 1 ea; br c, plug, electrical, mil-c-55116, u-229/u, 1 ea; br d, plug, electrical mil-c-55181, mw10mmd17, 1 ea; special features; molded crotch with transformer, mil-t-27, tf5rx1722

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A077a0