

View Online at <https://aerobasegroup.com/nsn/5995-01-042-5323>

**Special Features:**

M cable specification data: mil-c-13777, usaecom dwg sc-d-866286, sc-d-866293 conductor data: branches a, b, d neoprene jacket covering, 0.397 in. Diameter o/a, 600 vdc, 11 conductors, copper, stranded, no.22 awg with fep, insulation shield data: 2 conductors covered by separate shield, 11 conductors covered by shield branch c, poly vinyl jacket covering, 0.250 in diameter o/a, 600 vdc, 4 conductors, copper, stranded, no. 22 awg shield data: 2 conductors covered by separate shield, 4 conductors covered by shield dim. Data: branch a 12 inch from molded crotch branch b 6 foot from molded crotch branch c 11 inch from molded crotch branch d, 5 inch from molded tip terminal data: branch a, 1 each plug, electrical, burndy corp. Bt06a-12-10p branch b, 1 each plug, electrical, burndy corp. Bt06a-16-26s branch c, 1 each plug, electrical, mil-c-55116, u-220/u, branch d, 1 each plug, electrical mil-c-55181, mw10mmd17 special features: molded crotch with transformer, mil-t-27, tf5rx1722

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A077a0