Radio Frequency Cable Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5995-01-204-1460

| Cross Sectional Shape: |
|--|
| Round |
| Electrical Resistance: |
| 50.00 ohms impedance |
| Tempurature Rating: |
| -54.0 degrees celsius and 125.0 degrees celsius |
| Cross Section Outside Diameter: |
| 0.141 inches |
| End Application: |
| An/alr-46 test program set |
| Termination Type: |
| Connector plug both ends single conductor |
| Conductor Quantity: |
| 1 |
| Conductor Form: |
| Solid single conductor |
| Round Conductor Size: |
| 19 awg single conductor |
| Conductor Arrangement And Quantity: |
| 1 coaxial |
| Terminal Manufacturer Identifying Reference Number: |
| 160097p4 2nd end all conductors |
| Terminal Commercial And Government Entity Code: |
| 94117 both ends single conductor |
| Special Features: |
| Bend radius 0.375 3 bends |
| Material: |
| Steel 1st position conductor single conductor |
| Surface Treatment: |
| Tin core conductor single conductor |
| Surface Treatment Specification: |
| Mil-t-10727, type 1 military specification single treatment response core conductor single conductor |
| Fsc Application Data: |
| Test fixture, coupler |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A077a0 |



Mil-std (military Standard):

Mil-t-10727 spec.