Radio Frequency Cable Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5995-01-207-5194

| Cross Sectional Shape:   |
|--|
| Round  |
| Electrical Resistance:   |
| 50.00 ohms impedance   |
|  |
| Tempurature Rating:  |
| -54.0 degrees celsius and 125.0 degrees celsius Cross Section Outside Diameter:                      |
| 0.141 inches   |
|  |
| End Application:   |
| Test set, countermeasures an/usm-464   |
| Conductor Quantity:  |
|  |
| Conductor Form:  |
| Solid single conductor   |
| Round Conductor Size:  |
| 19 awg single conductor  |
| Conductor Arrangement And Quantity:  |
| 1 coaxial  |
| Terminal Manufacturer Identifying Reference Number:  |
| 160197p2 2nd end all conductors  |
| Terminal Commercial And Government Entity Code:  |
| 94117 both ends single conductor   |
| Material:  |
| Steel 1st position conductor single conductor  |
| Surface Treatment:   |
| Tin core conductor single conductor  |
| Surface Treatment Specification:   |
| Mil-t-10727, type 1 military specification single treatment response core conductor single conductor |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A077a0   |
| Mil-std (military Standard):   |
| Mil-t-10727 spec.  |
|  |