NSN 5995-01-234-0997

Radio Frequency Cable Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5995-01-234-0997

| Cross Sectional Shape: |
|--|
| Round |
| Overall Length: |
| 1.433 feet |
| Electrical Resistance: |
| 50.00 ohms impedance |
| Tempurature Rating: |
| -55.0 degrees celsius and 200.0 degrees celsius |
| Cross Section Outside Diameter: |
| 0.098 inches |
| End Application: |
| An/apx-76 radar |
| Termination Type: |
| Connector internal angle both ends single conductor |
| Conductor Quantity: |
| 1 |
| Strand Quantity Per Conductor: |
| 7 single conductor |
| Conductor Form: |
| Stranded single conductor |
| Round Conductor Size: |
| 24 awg single conductor |
| Strand Awg Size Per Conductor: |
| 34 single conductor |
| Conductor Arrangement And Quantity: |
| 1 coaxial |
| Terminal Manufacturer Identifying Reference Number: |
| 350909 2nd end all conductors |
| Terminal Commercial And Government Entity Code: |
| 80249 both ends single conductor |
| Special Features: |
| Rg316 cable and silicone compond and shrink tubing p/n460924-2 used on connectors |
| Material: |
| Steel 1st position conductor single conductor |
| Material Specification: |
| Mil-c-17 military specification single material response 2nd position cover single conductor |
| Precious Material And Location: |
| Conductor and shield silver |
| Precious Material And Weight: |
| 0.040 silver grains, troy |
| Precious Material: |
| |

Silver

NSN 5995-01-234-0997

Radio Frequency Cable Assembly - Page 2 of 2



| Surface Treatment: |
|--|
| Silver core conductor single conductor |
| Style Designator: |
| Dual internal angle connector |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A077a0 |

Mil-c-17 spec.

Mil-std (military Standard):