## NSN 5995-01-252-6568

Radio Frequency Cable Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5995-01-252-6568

| Cross Sectional Shape:   |
|--|
| Round  |
| Overall Length:  |
| 11.000 inches  |
| Electrical Resistance:   |
| 50.00 ohms impedance   |
| Tempurature Rating:  |
| -55.0 degrees celsius and 85.0 degrees celsius                                   |
| Cross Section Outside Diameter:  |
| 0.190 inches   |
| End Application:   |
| An/spg fire control radar  |
| Termination Type:  |
| Connector internal straight 2nd end single conductor                             |
| Conductor Quantity:  |
| 1  |
| Strand Quantity Per Conductor:   |
| 19 single conductor  |
| Criticality Code Justification:  |
| Feat   |
| Conductor Form:  |
| Stranded single conductor  |
| Round Conductor Size:  |
| 16 awg single conductor  |
| Strand Awg Size Per Conductor:   |
| 29 single conductor  |
| Conductor Arrangement And Quantity:  |
| 1 coaxial  |
| Terminal Manufacturer Identifying Reference Number:                              |
| T01 2nd end all conductors   |
| Terminal Commercial And Government Entity Code:                                  |
| 17217 both ends single conductor   |
| Special Features:  |
| Right angle sleeve marker reads (a1) j1  |
| Material:  |
| Plastic fluorinated ethylene propylene 4th position jacket single conductor      |
| Material Specification:  |
| Astm b298 assn standard single material response core conductor single conductor |
| Precious Material And Location:  |
| Conductor and shields silver   |
| Precious Material And Weight:  |
| 0.040 silver grains, troy  |

## NSN 5995-01-252-6568

A077a0

Radio Frequency Cable Assembly - Page 2 of 2

