

View Online at https://aerobasegroup.com/nsn/5995-01-283-0401

| Cross Sectional Shape: |
|--|
| Round |
| Overall Length: |
| 10.500 inches |
| Electrical Resistance: |
| 50.00 ohms impedance |
| Tempurature Rating: |
| -200.0 degrees celsius and 200.0 degrees celsius |
| Cross Section Outside Diameter: |
| 0.190 inches |
| End Application: |
| F-15 aircraft |
| Termination Type: |
| Connector internal straight both ends single conductor |
| Conductor Quantity: |
| 1 |
| Strand Quantity Per Conductor: |
| 19 single conductor |
| Conductor Form: |
| Stranded single conductor |
| Round Conductor Size: |
| 16 awg single conductor |
| Strand Awg Size Per Conductor: |
| 29 single conductor |
| Conductor Arrangement And Quantity: |
| 1 coaxial |
| Terminal Manufacturer Identifying Reference Number: |
| Z26 2nd end all conductors |
| Terminal Commercial And Government Entity Code: |
| 65474 both ends single conductor |
| Material: |
| Plastic polytetrafluoroethylene 1st position primary insulation single conductor |
| Material Specification: |
| Mil-i-23053/5 military specification single material response 4th position jacket single conductor |
| Precious Material And Location: |
| Conductor silver |
| Precious Material And Weight: |
| 0.040 silver grains, troy |
| Precious Material: |
| Silver |
| Surface Treatment: |
| Silver core conductor single conductor |
| |



Surface Treatment Specification:

Astm b298 assn standard single treatment response core conductor single conductor

Style Designator:

Internal connectors

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A077a0

Mil-std (military Standard):

Mil-i-23053 spec.