NSN 5995-01-323-3000

Cross Sectional Shape:

Round

N/a

Electrical Power Cable Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5995-01-323-3000

| Round | | | | |
|---|--|--|--|--|
| Extended Length: | | | | |
| 140.000 inches | | | | |
| Cross Section Outside Diameter: | | | | |
| 0.105 inches | | | | |
| Conductor Quantity: | | | | |
| 2 | | | | |
| Retracted Length: | | | | |
| 128.000 inches | | | | |
| Strand Quantity Per Conductor: | | | | |
| 19 all conductors | | | | |
| Conductor Form: | | | | |
| Stranded all conductors | | | | |
| Round Conductor Size: | | | | |
| 20 awg all conductors | | | | |
| Strand Awg Size Per Conductor: | | | | |
| 32 all conductors | | | | |
| Conductor Arrangement And Quantity: | | | | |
| 2 singles | | | | |
| Voltage Rating: | | | | |
| 600.0 root mean square (rms) operating voltage all conductors | | | | |
| Terminal Lug Aperture Size: | | | | |
| 0.201 inches 1st end all conductors | | | | |
| Special Features: | | | | |
| Primary insulation and jacket material conforms to I-p-403, type 3; special marking w1049 | | | | |
| Color: | | | | |
| Red 1st position cover first conductor | | | | |
| Material: | | | | |
| Plastic polytetrafluoroethylene 1st position primary insulation all conductors | | | | |
| Material Specification: | | | | |
| Astm b298 assn standard single material response core conductor all conductors | | | | |
| Precious Material And Location: | | | | |
| Internal surfaces silver | | | | |
| Precious Material: | | | | |
| Silver | | | | |
| Surface Treatment: | | | | |
| Silver core conductor all conductors | | | | |
| Surface Treatment Specification: | | | | |
| Astm b298 assn standard single treatment response core conductor all conductors | | | | |
| Shelf Life: | | | | |
| | | | | |

NSN 5995-01-323-3000

Electrical Power Cable Assembly - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A077a0