

View Online at https://aerobasegroup.com/nsn/5995-01-383-3120

| Cross Sectional Shape: |
|--|
| Round |
| Overall Length: |
| 4.000 inches |
| Electrical Resistance: |
| 50.00 ohms impedance |
| Tempurature Rating: |
| -55.0 degrees celsius and 200.0 degrees celsius |
| End Application: |
| 6625-01-260-9326; an/usd-9a guardrail |
| Termination Type: |
| Connector plug both ends single conductor |
| Conductor Quantity: |
| 1 |
| Strand Quantity Per Conductor: |
| 7 single conductor |
| Conductor Form: |
| Stranded single conductor |
| Round Conductor Size: |
| 28 awg single conductor |
| Strand Awg Size Per Conductor: |
| 38 single conductor |
| Material: |
| Plastic fluorinated ethylene propylene 3rd position jacket cable |
| Material Specification: |
| Mil-c-17/93-rg178 military specification all material responses core conductor cable |
| Precious Material And Location: |
| Conductor surface silver |
| Precious Material: |
| Silver |
| Surface Treatment: |
| Silver core conductor cable |
| Style Designator: |
| Internal and external angle connector |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A077a0 |
| |



Mil-std (military Standard):

Mil-c-17 spec.