NSN 5995-01-397-4092

Radio Frequency Cable Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5995-01-397-4092

Cross Sectional Shape
Cross Sectional Shape:
Round
Overall Length:
51.3 millimeters
Electrical Resistance:
50.00 ohms impedance
End Application:
C-130 aircraft support equipment
Termination Type:
Connector receptacle 1st end single conductor
Conductor Quantity:
1
Conductor Form:
Stranded single conductor
Round Conductor Size:
28 awg single conductor
Balance Coll
Material:
Plastic 1st position primary insulation single conductor
Plastic 1st position primary insulation single conductor
Plastic 1st position primary insulation single conductor Surface Treatment:
Plastic 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor
Plastic 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Style Designator:
Plastic 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Style Designator: Internal angle and internal straight connector
Plastic 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Style Designator: Internal angle and internal straight connector Shelf Life:
Plastic 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Style Designator: Internal angle and internal straight connector Shelf Life: N/a
Plastic 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Style Designator: Internal angle and internal straight connector Shelf Life: N/a
Plastic 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Style Designator: Internal angle and internal straight connector Shelf Life: N/a Unit Of Measure:
Plastic 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Style Designator: Internal angle and internal straight connector Shelf Life: N/a Unit Of Measure: Demilitarization:
Plastic 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Style Designator: Internal angle and internal straight connector Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli
Plastic 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Style Designator: Internal angle and internal straight connector Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:
Plastic 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Style Designator: Internal angle and internal straight connector Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig: