NSN 5995-01-463-3723

Branched Wiring Harness - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5995-01-463-3723

End Application: Bradley fighting vehicle (m2a3, m3a3)system 19207-12465333 Termination Type: Connector receptacle 8th end all conductors Binding Method: Taped Conductor Quantity: 2 Cable Assemblylength: 229,000 inches Branch Quantity: 16 Special Features: 11th end p12 connector external straight, 12th end p13 connector external straight, 13th end p2 connector external angle, 14th end p3 connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector include plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure:	
Termination Type: Connector receptacle 8th end all conductors Binding Method: Taped Conductor Quantity: 2 Cable Assemblylength: 2299.000 inches Branch Quantity: 16 Special Features: 11th end p12 connector external straight, 12th end p13 connector external straight, 13th end p2 connector external angle, 14th end p3 connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector include plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 asan standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	End Application:
Connector receptacle 8th end all conductors Binding Method: Taped Conductor Quantity: 2 Cable Assemblylength: 229.000 inches Branch Quantity: 16 Special Features: 11th end p12 connector external straight, 12th end p13 connector external straight, 13th end p2 connector external angle, 14th end p3 connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector include plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	Bradley fighting vehicle (m2a3, m3a3)system 19207-12465333
Binding Method: Taped Conductor Quantity: 2 Cable Assemblylength: 229.000 inches Branch Quantity: 16 Special Features: 11th end p12 connector external straight, 12th end p13 connector external straight, 13th end p2 connector external angle, 14th end p3 connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector include plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	Termination Type:
Taped Conductor Quantity: 2 Cable Assemblylength: 229.000 inches Branch Quantity: 16 Special Features: 11th end p12 connector external straight, 12th end p13 connector external straight, 13th end p2 connector external angle, 14th end p3 connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector include plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	Connector receptacle 8th end all conductors
Conductor Quantity: 2 Cable Assemblylength: 229.000 inches Branch Quantity: 16 Special Features: 11th end p12 connector external straight, 12th end p13 connector external straight, 13th end p2 connector external angle, 14th end p3 connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector included plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	Binding Method:
Cable Assemblylength: 229,000 inches Branch Quantity: 16 Special Features: 11th end p12 connector external straight, 12th end p13 connector external straight, 13th end p2 connector external angle, 14th end p3 connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector including plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	Taped
Cable Assemblylength: 229.000 inches Branch Quantity: 16 Special Features: 11th end p12 connector external straight, 12th end p13 connector external straight, 13th end p2 connector external angle, 14th end p3 connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector included plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	Conductor Quantity:
Branch Quantity: 16 Special Features: 11th end p12 connector external straight, 12th end p13 connector external straight, 13th end p2 connector external angle, 14th end p3 connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector include plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	2
Branch Quantity: 16 Special Features: 11th end p12 connector external straight, 12th end p13 connector external straight, 13th end p2 connector external angle, 14th end p3 connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector include plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	Cable Assemblylength:
Special Features: 11th end p12 connector external straight, 12th end p13 connector external straight, 13th end p2 connector external angle, 14th end p3 connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector included plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: —— Demilitarization:	229.000 inches
Special Features: 11th end p12 connector external straight, 12th end p13 connector external straight, 13th end p2 connector external angle, 14th end p3 connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector included plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	Branch Quantity:
11th end p12 connector external straight, 12th end p13 connector external straight, 13th end p2 connector external angle, 14th end p3 connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector included plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	16
connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector included plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	Special Features:
plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	11th end p12 connector external straight, 12th end p13 connector external straight, 13th end p2 connector external angle, 14th end p3
Material: Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	connector external straight, 15th end p10 connector external straight, 16th end j3 connector external straight, 7th end p9 connector includes
Tin 2nd position shield braid, metallic cable Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	plug, backshell 90 degrees on connectors p2, p10, p11. 16th j3 connector with test terminator b
Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	Material:
Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	Tin 2nd position shield braid, metallic cable
Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	Material Specification:
Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:	Astm b33 assn standard all material responses core conductor all conductors
Shelf Life: N/a Unit Of Measure: Demilitarization:	Surface Treatment:
N/a Unit Of Measure: Demilitarization:	Tin core conductor all conductors
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
No	Demilitarization:
	No
Fiig:	Fiig:
A077a0	A077a0