Electrical Power Cable Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5995-01-493-1870

Cross Sectional Shape:

Round

Overall Length:

205.000 inches

Tempurature Rating:

-55.0 degrees celsius and 150.0 degrees celsius

Outside Diameter:

0.210 inches single conductor

Environmental Protection:

Chemical resistant and moisture resistant and salt air resistant

End Application:

Step down transformer

Termination Type:

Connector internal straight both ends single conductor

Conductor Quantity:

1

Conductor Form:

Braid, tubular single conductor

Product Name:

Flexible cables (90 series)

Conductor Cross-sectional Shape:

Tubular braid single conductor

Voltage Rating:

6000.0 root mean square (rms) operating voltage single conductor

Special Features:

Frequency range & highest power rating - 26ghz; 150lbs/in compression strenght; 40lbs connector retention; bend radius of 1.00 in.

Material:

Silver 1st position primary insulation single conductor

Material Specification:

Astm-b-298 assn standard single material response 1st position primary insulation single conductor

Precious Material And Location:

Conductor insulation silver

Precious Material:

Silver

Style Designator:

Straight

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5995-01-493-1870

Electrical Power Cable Assembly - Page 2 of 2

Fiig: A077a0

