

View Online at <https://aerobasegroup.com/nsn/5995-01-509-4007>

Cross Sectional Shape:

Round

Cross Section Outside Diameter:

0.187 inches

End Application:

F5b flight simulator

Product Name:

Hyper plus cables

Round Conductor Size:

24 awg single conductor

Special Features:

Tek pack box; guaranteed to exceed next and acr by 4db; ideal for 100 mbps tpddi, 155 mbps atm, 802.3, 802.5 802.12 isdn and voice applications; acr min 66 db at 0.772 mhz to 14 db at 100 mhz; attenuation 1.8 at 0.772 mhz to 22 at 100 mhz; cable type 4 pair, utp, solid; construction pvc, fr pvc jacket, pe insulation; plenum fep insulation, polymer alloy jacket; impedance, ohms, 102 porm 15 pct at 0.772 mhz; 100 porm 15 pct at 100 mhz; dc resistance 9.38 ohms/100 m max; plenum 0.172 inch; frequency 0.772 mhz to 100 mhz; mutual capacitance, max, 17.1 pf/ft; 5.6 nf/100m; nom velocity of propagation pct pvc 72; plenum 70; ps next min 68db at 0.772 mhz; 36 db at 100 mhz; worst pair next, min db, 9.38 ohms/100m; skew, max, 18 ns/100m; standards meetseia/tia 568a; weight pvc 22 lb/1000 ft; plenum 21 lb/1000 ft; warran type 15 years

Fsc Application Data:

Category 5 cable for 100 mbps networks

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A077a0