NSN 5995-01-521-6746

Electrical Ribbon Cable Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5995-01-521-6746

Cross-sectional Width: 2.660 inches End Application: An/tsm-19 (v) 5 electronics shop, transportable Center To Center Distance Between Terminal Holes: 0.100 inches Termination Type: Connector plug both ends all conductors Conductor Quantity: 50 Conductor Form: Solid all conductors Product Name: Cable assembly, digital, i/o Special Features: Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inches labeled p1-1 to jgd1-1 of a2a5. Label b is to be located 24.0 inches from p-2 (plus / minus 1 inch) and is to be labeled	
End Application: An/tsm-19 (v) 5 electronics shop, transportable Center To Center Distance Between Terminal Holes: 0.100 inches Termination Type: Connector plug both ends all conductors Conductor Quantity: 50 Conductor Form: Solid all conductors Product Name: Cable assembly, digital, i/o Special Features: Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inches)	
An/tsm-19 (v) 5 electronics shop, transportable Center To Center Distance Between Terminal Holes: 0.100 inches Termination Type: Connector plug both ends all conductors Conductor Quantity: 50 Conductor Form: Solid all conductors Product Name: Cable assembly, digital, i/o Special Features: Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inches	
Center To Center Distance Between Terminal Holes: 0.100 inches Termination Type: Connector plug both ends all conductors Conductor Quantity: 50 Conductor Form: Solid all conductors Product Name: Cable assembly, digital, i/o Special Features: Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inches	
O.100 inches Termination Type: Connector plug both ends all conductors Conductor Quantity: 50 Conductor Form: Solid all conductors Product Name: Cable assembly, digital, i/o Special Features: Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inches	
Termination Type: Connector plug both ends all conductors Conductor Quantity: 50 Conductor Form: Solid all conductors Product Name: Cable assembly, digital, i/o Special Features: Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inches)	
Connector plug both ends all conductors Conductor Quantity: 50 Conductor Form: Solid all conductors Product Name: Cable assembly, digital, i/o Special Features: Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inches)	
Conductor Quantity: 50 Conductor Form: Solid all conductors Product Name: Cable assembly, digital, i/o Special Features: Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inches	
Conductor Form: Solid all conductors Product Name: Cable assembly, digital, i/o Special Features: Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inches	
Conductor Form: Solid all conductors Product Name: Cable assembly, digital, i/o Special Features: Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inches	
Solid all conductors Product Name: Cable assembly, digital, i/o Special Features: Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inch	
Product Name: Cable assembly, digital, i/o Special Features: Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inches	
Cable assembly, digital, i/o Special Features: Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inches).	
Special Features: Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inch	
Cable is to be wrapped in 3 locations with tedlar tape for labeling. Label a is to be located 6.0 inches from p-1 (plus / minus 1 inch	
be labeled p1-1 to jgd1-1 of a2a5. Label b is to be located 24.0 inches from p-2 (plus / minus 1 inch) and is to be labeled	and is to
. "	
26916-087-019605-012. Label c is to be located 6.0 inches from p-2 (plus / minus 1 inch) and is to be labeled p2-1 to j44-1. Cable	
identification shall be marked as shown in table 1 of drawing 087-019605 cage code 26916 and marked using contrasting ink iaw	
mil-std-130.	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A077a0	