

View Online at <https://aerobasegroup.com/nsn/5995-01-521-8625>

End Application:

Wsd 39a

Center To Center Distance Between Terminal Holes:

0.100 inches

Termination Type:

Connector receptacle both ends all conductors

Conductor Quantity:

25

Conductor Form:

Solid all conductors

Product Name:

Cable assembly tlc 50 ohm

Round Conductor Size:

30 awg all conductors

Conductor Arrangement And Quantity:

25 molded

Special Features:

Housing contains standard pressure copper alloy receptacle contacts plated with .000030 min inch thick gold over .000050 min inch thick nickel in mating area; p2 connector must mate and latch to amp part no 1-102158-0; p1 and p2 housing shall be thermoplastic; the housing is a 50 position header; pull tabs shall be provided; the cable shall be 50 ohm transmission line cable; 25 signal conductors; 50 grnd conductors 32 awg silver plated copper; 50 +-5 ohm impedance; 28 pico-farads per foot capacitance; 14 nanoseconds per foot propagation delay; pin 1 shall be clearly identified on p1 and p2; resistance of cable assembly shall be less than .21ohms for signal conductors and less than .18 ohms for grnd conductors; cable assemblies shall be able to withstand 300 vdc between any adjacent signal and/or grnd paths; impedance of assembly shall be 50 +-5 ohms

Material:

Silver alloy core coating all conductors

Precious Material And Location:

All connector ends plated with 0.000050 inches thick gold and all conductors silver plated silver

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A077a0