

View Online at <https://aerobasegroup.com/nsn/5995-01-521-8633>

End Application:

Wsd 39a

Center To Center Distance Between Terminal Holes:

0.100 inches

Termination Type:

Connector receptacle both ends all conductors

Conductor Quantity:

25

Conductor Form:

Solid all conductors

Product Name:

Cable assembly tlc 50 ohm

Round Conductor Size:

30 awg all conductors

Conductor Arrangement And Quantity:

25 molded

Special Features:

Connector contains standard pressure copper alloy receptacle contacts plated with .000030 min inch thick gold over .000050 inch min thick nickel in mating area; p2 conn must mate and latch to amp part no 1-1021258-0; p1 and p2 conn housing shall be thermoplastic; conn shall be 50 position header; pull tabs shall be provided; cable shall be 50 ohm transmission line cable; 25 signal conductors 30 awg silver plated copper; 50 grd conductors 32 awg silver plated copper; 50 +-5 ohm impedance; 28 pico-farads per ft impedance; 14 nanoseconds per foot propagation delay; pin 1 shall be clearly identified on connectors p1 and p2; resistance of cable assembly shall be less than .21 ohms for signal conds and less than .18 ohms for grd conds; cable assemblies shall be able to withstand 300 vdc between any adjacent signal and/or grd paths; impedance of cable assembly shall be 50 +-5 ohms

Material:

Copper core conductor all conductors and silver core conductor all conductors

Precious Material And Location:

Receptacle contacts plated with .000030 inch thick min gold and all conductors silver plated silver

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A077a0